

In case of consideration for using Autom otive equipm ent/device which dem and high reliability, kindly contactour sales w indow correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		QT	AT	
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ^{(1) (2)}	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽³⁾				
	OPERATING HUMIDITY RANGE	RH 85 % MAX ^{(2) (4)}	STORAGE HUMIDITY RANGE	RH 70 % MAX ^{(3) (4)}				
	VOLTAGE	60 V AC ⁽⁵⁾	CURRENT	0.5A ⁽⁵⁾				
APPLICABLE CABLE		FFC ⁽⁶⁾						
SPECIFICATIONS								
ITEM	TEST METHOD			REQUIREMENTS		QT	AT	
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		x	x	
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.		x	x	
MARKING	CONFIRMED VISUALLY.					x	x	
ELECTRIC CHARACTERISTICS								
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)	80 mΩ MAX. ⁽⁷⁾				x		
INSULATION RESISTANCE	100 V DC.	500 MΩ MIN.				x		
VOLTAGE PROOF	200 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.				x		
MECHANICAL CHARACTERISTICS								
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE: 25.5 N MAX. WITHDRAWAL FORCE: 2.55 N MIN.		x		
MECHANICAL OPERATION	50 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: NO VARIATION OF 20 mΩ OR MORE FROM INITIAL VALUE. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x		
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGL AMPLITUDE : 0.75 mm, AT 2 h FOR 3 DIRECTION.			① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x		
SHOCK	490 ms ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.					x		
LOCK STRENGTH	MATE TO APPLICABLE CONNECTOR AND APPLY PULL FORCE HORIZONTALLY.			30 N MIN.		x		
FFC RETENTION FORCE	ASSEMBLE APPLICABLE FFC AND PULL HORIZONTALLY WITH 10mm/min IN MATTING DIRECTION.			10 N MIN. ⁽⁸⁾		x		
ENVIRONMENTAL CHARACTERISTICS								
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.			① CONTACT RESISTANCE: NO VARIATION OF 20 mΩ OR MORE FROM INITIAL VALUE. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x		
DRY HEAT	EXPOSED AT 85±2 °C, 96 h							
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→+5~+35→+85→+5~+35°C TIME 30→ 5 MAX→ 30→5 MAX min. UNDER 5 CYCLES.					x		
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			① CONTACT RESISTANCE: NO VARIATION OF 20 mΩ OR MORE FROM INITIAL VALUE. ② NO DEFECT SUCH AS CORROSION WHICH IMPAIRS THE FUNCTION OF CONNECTOR.		x		
SULFUR DIOXIDE	EXPOSED IN 25 PPM FOR 96 h. (TEST STANDARD: JIS C 60068)					x		
REMARKS		① INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING. ② OPERATING TEMPERATURE SHOULD BE -55 TO 40 °C, WHEN HUMIDITY EXCEEDS 80% RH ③ THE SPECIFICATION IS APPLIED TO THE PRE-ASSEMBLED COMPONENT AND THE CABLE ASSEMBLED PRODUCT BOTH IN DELIVERY AND STORAGE, BEFORE ASSEMBLED TO PCB. ④ THERE MUST NOT BE DEWFALL. ⑤ IT IS THE MAXIMUM VALUE OF CONNECTOR, CONFIRM THE SPECIFICATION OF THE CABLE. ⑥ ONLY FFC THAT PROCESSES THE TERMINAL THAT WE SPECIFIED. ⑦ DON'T INCLUDE CONDUCTOR RESISTANCE OF CABLE.		APPROVED	HS. OKAWA	09.11.24		
△		DESIGNED		CHECKED				
COUNT		DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	DATE	
△								
<p>Note QT: Qualification Test AT: Assurance Test X: Applicable Test</p> <p>Unless otherwise specified, refer to JIS-C-5402.</p>								
HRS		SPECIFICATION SHEET		DRAWING NO.		ELC4-327150-00		
HIROSE ELECTRIC CO., LTD.		PART NO.		DRAWING NO.		FX16M2-51P-HC		
		CODE NO.		DRAWING NO.		CL575-3263-0-00		
						AH. EDASHIGE 09.11.20		
						AH. EDASHIGE 09.11.20		
						AH. EDASHIGE 09.11.20		
						09.11.20		
						1/1		