

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	
		-25°C TO +85°C		-25°C TO +60°C	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS		QT	AT
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		X	X
MECHANICAL CHARACTERISTICS					
VIBRATION	FREQUENCY 10 TO 55 Hz	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
	SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES. <input type="checkbox"/> 1			X	-
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. <input type="checkbox"/> 1	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
				X	-
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C	NO HEAVY CORROSION THAT LOSE FUNCTION.		X	-
	TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.			X	-
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.			X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
<input type="checkbox"/> 1					
REMARK					
<input type="checkbox"/> 1 EXAMINATION IS HELD WITH "DH80A- * * P".					
Unless otherwise specified, refer to JIS C 5402 .					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-127363-00	
HRS		SPECIFICATION SHEET		PART NO.	
		HIROSE ELECTRIC CO., LTD.		CODE NO.	
				DH80A-SCREW	
				CL244-0059-4-00	
				<input type="checkbox"/> 1/1	