# 3-647002-2 ACTIVE

#### MTA 100

TE Internal #: 3-647002-2

Standard Rectangular Connectors, Connector Assembly, Plug, Mating Alignment, Polarization Mating Alignment Type, Mating


Retention, MTA 100

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors > MTA Plug: Nylon, Tin Plated, 2.54 mm, with Mating Alignment











Connector Product Type: Connector Assembly

Connector & Housing Type: Plug

Mating Alignment: With

Mating Alignment Type: Polarization

Mating Retention: With

All MTA Plug: Nylon, Tin Plated, 2.54 mm, with Mating Alignment (28)

# **Features**

# **Product Type Features**

Compatible With Discrete Wire Type	Stranded
Connector Product Type	Connector Assembly
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Insertion Force Type	Normal
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Footures	

## **Configuration Features**

Number of Cavities	2
Contacts Preloaded	Yes
Number of Positions	2
Number of Rows	1



#### **Electrical Characteristics**

Electrical Characteristics	
Operating Voltage	250 VAC
Contact Features	
Contact Type	Tab
Wire Contact Termination Area Plating Material	Tin
Contact Underplating Material	Nickel
Contact Mating Area Plating Material	Tin
Contact Retention Within Housing	With
Contact Current Rating (Max)	5 A
Termination Features	
Termination Method to Wire & Cable	Insulation Displacement (IDC)
Mechanical Attachment	
Contact Retention Type Within Housing	Locking Lance
Mating Alignment	With
Mating Alignment Type	Polarization
Mating Retention	With
Mating Retention Type	Latch
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Nylon 6/6
Housing Color	Blue
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Connector Height	12.54 mm[.494 in]
Product Width	21.4 mm[.843 in]
Product Length	7.62 mm[.3 in]
Wire Size	.12 – .15 mm²
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Shielded	No
Circuit Application	Signal



#### **Industry Standards**

CSA Rating	LR 7189
UL Rating	Recognized
Agency/Standard	CSA, UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-2

### **Packaging Features**

Packaging Quantity	300
Packaging Method	Bag/Box

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





TE Part # CAT-104MTA-NTPNR
MTA Receptacle: Nylon, Tin Plated,
2.54 mm



TE Part # 640550-2 02P MTA100 COVER



TE Part # CAT-104MTA-NYLCC Nylon PCB Connector Covers: 2.54 mm, MTA 100





TE Part # 3-644574-2 02P MTA100 CONN ASSY BLK LF



TE Part # 58638-1 MTA 100 CRIMP HEAD PRODUCTION POSTED



TE Part # 58639-1 MTA 100 POSTED MANUAL TOOL ASSEMBLY

# Also in the Series | MTA 100



Insertion & Extraction Tools(2)



PCB Connector Covers(69)



PCB Connector Keying(1)



PCB Headers & Receptacles(440)



Standard Rectangular Connectors (495)



Wire-to-Board Connector Assemblies & Housings(1)



Wire-to-Board Connector Contacts(8)


# Customers Also Bought



TE Part #3-640441-3 MTA Receptacle: Nylon, Tin Plated, 2.54 mm



TE Part #3-647000-2 02P MTA100 PSTD CONN ASSY LF



TE Part #3-520117-2 ULTRAFAST 250 ASSY REC 16-14 TPBR LP



TE Part #5-103957-7
2X8 MTE RCPT SR LATCH .100CL



## **Documents**

# **Product Drawings**

02P MTA100 PSTD CONN ASSY LF

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_3-647002-2\_D.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_3-647002-2\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_3-647002-2\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Product Specifications**

**Application Specification** 

English

## **Agency Approvals**

Agency Approval Document

English