

APPLICABLE STANDARD				STORAGE TEMPERATURE RANGE		-10 °C TO +60°C (NOTE3)	
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +105°C (NOTE1)		STORAGE TEMPERATURE RANGE			
	OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)		STORAGE HUMIDITY RANGE			40% TO 70% (NOTE3)
	APPLICABLE CONNECTOR	DF62B-5EP-2.2C(##)		VOLTAGE			AC/DC 250V
APPLICABLE CONTACT	DF62-22SC* DF62-2428SC* DF62-30SC*		CURRENT			AWG 22 : 3A AWG 24 : 2A AWG 26-30 : 1A	
SPECIFICATIONS							
ITEM	TEST METHOD			REQUIREMENTS		QT	AT
CONSTRUCTION							
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.		X	X
MARKING	CONFIRMED VISUALLY.					X	X
ELECTRIC CHARACTERISTICS							
INSULATION RESISTANCE	500 V.DC.			1000 MΩ MIN.			X
VOLTAGE PROOF	650 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			X
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION	30 TIMES INSERTION AND EXTRACTION.			NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.			NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES EACH FOR 3 BOTH AXIAL DIRECTIONS.			NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2°C , 90 TO 95 % , 96 h. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)			①INSULATION RESISTANCE: 1000 MΩ MIN. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55°C→ +85°C TIME 30min→ 30min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE TANK IS 2~3 min) (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)			①INSULATION RESISTANCE: 1000 MΩ MIN. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X
NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT. NOTE2:NO CONDENSING NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFOR PCB ON BOARD, AFTER PCB ON BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STRAGE DURING TRANSPORTATION.							
△	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
REMARKS							
Unless otherwise specified, refer to JIS C 5402.				APPROVED	KI. AKIYAMA	13.09.17	
				CHECKED	OM. MIYAMOTO	13.09.13	
				DESIGNED	TH. YOSHI ZAWA	13.09.13	
				DRAWN	MI. SAKIMURA	13.09.09	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-351973-01				
HRS		SPECIFICATION SHEET		PART NO.	DF62C-5S-2.2C(11)		
		HIROSE ELECTRIC CO., LTD.		CODE NO.	GL544-0568-2-11		△
							1/1