

6 INCHES LENGTH



Connector A  
132119  
SMA Jack Straight  
Bulkhead - Rear Mount Brass Gold + Heatshrink

50 Ohm RG-174  
Continuity/Hi-Pot

Connector B  
142252  
SMB Jack Right Angle  
Brass Gold + Heatshrink

**Assembly & Label Notes**

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink  
Assembly shall be built with SN96.5 LEAD FREE solder.  
See Routing Notes for additional assembly & testing instructions.



Connector A	Cable	Connector B
<b>Part #:</b> 132119 <b>Description:</b> SMA BHD JK RG174 RG188 RG316 50O <b>Type:</b> SMA <b>Gender:</b> Jack <b>Body Type:</b> Straight <b>Contact Type:</b> Solder <b>Polarity:</b> Standard <b>Impedance:</b> 50 Ohm <b>Mounting:</b> Bulkhead - Rear Mount <b>Body Material:</b> Brass <b>Body Finish:</b> Gold <b>IP Rating:</b> None <b>Contact Material:</b> Beryllium Copper <b>Contact Finish:</b> Gold <b>Max. Freq.:</b> 12.4 GHz <b>Booting:</b> SMA Jack Straight BHD	<b>Part #:</b> RG-174 <b>Description:</b> RG-174 - PE 0.1 <b>Dielectric:</b> PE <b>Shielding:</b> Braid <b>Diameter:</b> 0.1 <b>Impedance:</b> 50 Ohm <b>Sheathing:</b> None <b>Testing:</b> Continuity Hi-Pot <b>Length:</b> 6 Inches	<b>Part #:</b> 142252 <b>Description:</b> SMB R/A JK RG174 RG316 LMR100 50O <b>Type:</b> SMB <b>Gender:</b> Jack <b>Body Type:</b> Right Angle <b>Contact Type:</b> Solder <b>Polarity:</b> Standard <b>Impedance:</b> 50 Ohm <b>Mounting:</b> Cable <b>Body Material:</b> Brass <b>Body Finish:</b> Gold <b>IP Rating:</b> None <b>Contact Material:</b> Brass <b>Contact Finish:</b> Gold <b>Max. Freq.:</b> 4 GHz <b>Booting:</b> SMB Jack Right Angle <b>Clocking:</b> 0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:  
**SMA-ST-JK/SMB-RA-JK G174 6I**

Part No:  
**Q-2W03100030061**

**UNLESS SPECIFIED**  
TOLERANCE:  
0-18 inches +/- 1/2"  
over 18" +/- 2%  
ASSEMBLY:  
CENTER LABEL IF LENGTH  
IS LESS THAN 12 INCHES