



|      |      |    |    |    |    |    |    |    |    |    |    |      |    |    |    |    |      |    |    |    |
|------|------|----|----|----|----|----|----|----|----|----|----|------|----|----|----|----|------|----|----|----|
| PIN  | 1    | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10 | 11 | 12   | 13 | 14 | 15 | 16 | 17   | 18 | 19 | 20 |
| COM1 | COM1 | 1G | 1E | 1D | 1C | 2E | 2D | 2C | 3E | 3D | 3C | P1   | 4E | 4D | 4C | P2 | 5E   | 5D | 5C | 5B |
| PIN  | 21   | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32   | 33 | 34 | 35 | 36 | 37   | 38 | 39 | 40 |
| COM1 | 5A   | 5F | 5G | 4B | 4A | 4F | 4G | 3B | 3A | 3F | 3G | COL2 | 2B | 2A | 2F | 2G | COL1 | 1B | 1A | 1F |

NOTES:

- |                                           |                               |
|-------------------------------------------|-------------------------------|
| 1. DISPLAY TYPE: TN                       | 5. OPERATING VOLTAGE: 5.0 V   |
| 2. VIEWING DIRECTION: 6:00                | 6. OPERATING TEMP: -30°C~80°C |
| 3. POLARIZER MODE: POSITIVE/TRANSFLECTIVE | 7. STORAGE TEMP: -30°C~80°C   |
| 4. DRIVER METHOD: STATIC                  | 8. CONNECTOR: PIN             |