



F1-RMS01RU2X

FEATURES

- Swing Out Shelf
- Holds (2) LGX Adapter Plates, Cassettes, or Modules
- Multiple Tie Downs and Cable Retention Brackets
- Flush Mount or 3.5" Protrusion; No Accessories Required
- Order Preloaded with Terminated Cables, Adapters, Pigtails or Cassettes
- Rugged 14 Gauge Aluminum, Available in Black or Off-White (BW)

The 1RU FIS Swing Out Patch Panel accommodates (2) LGX adapter plates, modules or cassettes. It is designed to house fiber terminations and accommodate patching of fiber links. The swing-out design offers easy access to cable and splices located in the patch and splice bay. Multiple cable retention brackets and tie down spots allow for convenient cable management. These units can be flush mounted or mounted with 3.5" protrusion from the rack with no additional accessories. Rack mount installs into a standard 19" rack with included mounting hardware. Adapter panels and 23" mounting brackets are sold separately.

SPECIFICATIONS

Dimensions	17"W x 11.5" D x 1.75"H
Capacity	Up to 12 (6 Pack) or 16 (8 Pack) Simplex Connections Up to 24 (6 Pack) Duplex Connections (LC or SC)
Material	.060" Aluminum
Coatings	Electro-statically Applied Powder Coat, Available in Black or Off White

ORDERING INFORMATION

F1-RMS01RU2X	1RU Swing Out Enclosure, 2 Plates, Black
F1-RMS01RU2X-BW	1RU Swing Out Enclosure, 2 Plates, Off White

ACCESSORIES (PURCHASED SEPARATELY)

RACK-ADP23	1RU and 2RU 23" Rack Mounting Brackets, Pair, Black
RACK-ADP23BW	1RU and 2RU 23" Rack Mounting Brackets, Pair, Off White
F1-SPL12	Metal Splice Tray, 12 Position Fusion Splice Chip, 6.5"L x 4.7"W x .42"H
F1-SPL24	Metal Splice Tray, 24 Position Fusion Splice Chip, 11.72"L x 3.99"W x .42"H
F1-6808	Plastic Splice Tray, 12 Position Fusion Splice Chip, 7.1"L x 4.25"W x .48"H
F1-6707BLKF	Metal Splice Tray, 12 Position Fusion Splice Chip, 7.5"L x 4"W x .63"H