PROPRIETARY INFORMATION:								REVISION				
PROPRIETARY OF GLOBTEK, INC. ANY RE									DESCRIPTION DATE APPRO			
	USE OF THIS DRAWING, IN WHOLE OR I PROHIBITED EXCEPT AS SPECIFIED IN '						А		INITIAL RELEASE, RFS. 26529, BS	10/31/16	HM	
											I	
1830+150,-0												
USC-A	4 1 A-SP											
5	PE		PVC 45P-RO White									
4	Tin		0D:1.0mm-R0						Barrel Locking Notch			
3	Со											
2									Ø2.1 ^{+0.1}			
No	Title Description								Ø5.5±0.05			
PACKING: HANKING, 400pcs PER MASTER CARTON 110±10 110±10 NOTES: 1. Polarity is determinated when the USB cab connected to the PCB. RELEASED By N.Frost at 11:07 am, C								2016	Pin outUSC-A-SPBarrel 5.5*2.1*10. $1 - Red$ 1Center $2 - White$ 23 $3 - Green$ 3Blunt Cut $4 - Black$ 5Outside Barrel 5ShellDrain+BraidShellBlunt Cut			
and the state of t					DASH NO.	PART NO	REV.		DESCRIPTION		NOTES	
									TABULATION BLOCK			
CRoHS -						TOLER DECIMALS .xx +/- 0.1 .xxx +/005			ANGULAR +/- 1' www.globtek.com ANGULAR He GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 0764 Tel. 201-784-1000 Fax 201.784.011			
			c. will not be liable for the	Limitation of Use: Globtek product are not authorized for use as	INIT.BY: BS DATE: 10/31/16 MILLIMETER .xx +/- 0.3 .xxx +/013			+/- 1°	DWG TITLE: USC-BARREL L=1830 mm, 5.5*2.1*	10, White		
Contents of this document are subject to change without prior notice		safety and performance of these power product if unauthorized access and repair occurs. End user should consult the appli ble UL,CSA or EN Standards for proper		mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	DRAWN: NF	DATE: 10/31/16	FSCN No.: G, YL	SIZE A			REV. A	
			instruction.		APRVD: BS	DATE: 10/31/16	SCALE: N	ONE	PART NO: USBA1M8C10WH(R)		SHEET 1/1	