



- 1 HOUSING & EJECT LATCHES: PBT, UL94V-0, COLOR BLUE. POSTS: PHOSPHOR BRONZE.
- 2 POSTS: 0.00076[.000030] MIN GOLD ON MATING AREA, 0.00254[.000100] MIN TIN ON SOLDER END, ALL OVER 0.00127[.000050] MIN NICKEL ON ENTIRE POST.
- 3 DATUMS S & T TO BE ESTABLISHED BY CUSTOMER.
- 4 LONG EJECT LATCHES FOR MATING IDC/AMP-LATCH STYLE RECEPTACLES WITH A STRAIN RELIEF
- 5 MANUFACTURER'S LOGO TO BE LOCATED IN APPROXIMATE AREA SHOWN.

	D	C	B	A	NO OF POS	PART NUMBER
OBSELETE	78.74 [3.100]	31	86.36 [3.400]	100.33 [3.950]	64	1-1761690-7
OBSELETE	73.66 [2.900]	29	81.28 [3.200]	95.25 [3.750]	60	1-1761690-6
OBSELETE	60.96 [2.400]	24	68.58 [2.700]	82.55 [3.250]	50	1-1761690-5
OBSELETE	48.26 [1.900]	19	55.88 [2.200]	69.85 [2.750]	40	1-1761690-3
OBSELETE	40.64 [1.600]	16	48.26 [1.900]	62.23 [2.450]	34	1-1761690-1
OBSELETE	35.56 [1.400]	14	43.18 [1.700]	57.15 [2.250]	30	1-1761690-0
	30.48 [1.200]	12	38.10 [1.500]	52.07 [2.050]	26	1761690-9
OBSELETE	27.94 [1.100]	11	35.56 [1.400]	49.53 [1.950]	24	1761690-8
OBSELETE	22.86 [0.900]	9	30.48 [1.200]	44.45 [1.750]	20	1761690-7
OBSELETE	17.78 [0.700]	7	25.40 [1.000]	39.37 [1.550]	16	1761690-6
OBSELETE	15.24 [0.600]	6	22.86 [0.900]	36.83 [1.450]	14	1761690-5
OBSELETE	12.70 [0.500]	5	20.32 [0.800]	34.29 [1.350]	12	1761690-4
OBSELETE	10.16 [0.400]	4	17.78 [0.700]	31.75 [1.250]	10	1761690-3
OBSELETE	10.16 [0.400]	3	15.24 [0.600]	29.21 [1.150]	8	1761690-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN 9131 CRISAMORE/D1 OSJUNOS  
 CJK S.BOLASH OSJUNOS  
 APD M.WALMSLEY OSJUNOS

TE Connectivity

NAME: HEADER ASSEMBLY, LONG EJECT LATCHES, RIGHT ANGLE, LOW PROFILE, IDC

PRODUCT SPEC: -

APPLICATION SPEC: -

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 1761690

RESTRICTED TO: -

WEIGHT: 0.000000

CUSTOMER DRAWING

SCALE: 4:1 SHEET: 1 OF 1 REV: B1