



Key-operated switch O.M.R, 22 mm, round, metal, shiny, lock number 73034, black, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, key removal O, with laser labeling, upper case and lower case, always upper case at the beginning of the word

|  |  |
|--|--|
| product brand name                                 | SIRIUS ACT   |
| product designation                                | Key-operated switches  |
| design of the product                              | Actuating/signaling element  |
| product type designation                           | 3SU1   |
| product line                                       | Metal, shiny, 22 mm  |
| manufacturer's article number of included key      | <a href="#">3SU1950-0FL10-0AA0</a>   |
| <b>Actuator</b>                                    |  |
| principle of operation of the actuating element    | latching, 90° (10:30 h/13:30 h)  |
| product extension optional light source            | No   |
| color  |  |
| • of the actuating element                         | silver   |
| material of the actuating element                  | metal  |
| shape of the actuating element                     | Key  |
| outer diameter of the actuating element            | 29.5 mm  |
| marking of the actuating element                   | Any inscription, text in upper/lower case, all words begin with upper case letters |
| number of switching positions                      | 2  |
| switch position for key distraction                | O  |
| actuating angle                                    |  |
| • clockwise  | 90°  |
| lock make  | O.M.R.   |
| key number   | 73034  |
| <b>Front ring</b>                                  |  |
| product component front ring                       | Yes  |
| design of the front ring                           | Standard   |
| material of the front ring                         | Metal, high gloss  |
| color of the front ring                            | silver   |
| <b>General technical data</b>                      |  |
| protection class IP                                | IP66, IP67, IP69(IP69K)  |
| • of the terminal                                  | IP20   |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13   |
| shock resistance                                   |  |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms   |
| vibration resistance                               |  |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g  |
| operating frequency maximum                        | 1 800 1/h  |
| mechanical service life (switching cycles) typical | 300 000  |
| reference code according to IEC 81346-2            | S  |
| Substance Prohibitance (Date)                      | 10/01/2014   |

| Ambient conditions   |  |
|--|--|
| <b>ambient temperature</b>   |  |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul> | -25 ... +70 °C<br>-40 ... +80 °C                                   |
| environmental category during operation according to IEC 60721                             | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| Installation/ mounting/ dimensions   |  |
| <b>height</b>  | 29.5 mm  |
| <b>width</b>   | 29.5 mm  |
| <b>shape of the installation opening</b>   | round  |
| <b>mounting diameter</b>   | 22.3 mm  |
| <b>positive tolerance of installation diameter</b>   | 0.4 mm   |
| <b>mounting height</b>   | 51.7 mm  |
| <b>installation width</b>  | 29.5 mm  |
| <b>installation depth</b>  | 25.4 mm  |
| Certificates/ approvals  |  |
| Further information  |  |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-4HF01-0AA0-Z Y15>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-4HF01-0AA0-Z Y15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-4HF01-0AA0-Z Y15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1050-4HF01-0AA0-Z Y15&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-4HF01-0AA0-Z Y15&lang=en)

last modified:

1/26/2022 