

**Cable glands
VG 9-K68 SKS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Cable gland with spiral kink protection specially for flexible connections

General ordering data

| | |
|------------|---|
| Order No. | 1720480000 |
| Type | VG 9-K68 SKS |
| Version | Cable gland, Polyamide 6, RAL 7035, External thread: PG 9 |
| GTIN (EAN) | 4008190358693 |
| Qty. | 50 pc(s). |

**Cable glands
VG 9-K68 SKS**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------|-------|------------|--------|
| Length | 79 mm | Net weight | 10.5 g |
|--------|-------|------------|--------|

General information

| | | | |
|-------------------------------------|-------------|-------------------------------------|-------------------------|
| AF size 1 | 19 mm | Cable gland | PG |
| Clamping range, max. | 8 mm | Clamping range, min. | 4 mm |
| Colour code | RAL 7035 | DIN | EN 50262 (for M thread) |
| External thread | PG 9 | Length of thread | 8 mm |
| Material | Polyamide 6 | Operating temperature range, max. | 80 °C |
| Operating temperature range, min. | -30 °C | Seal insert | CR |
| Torque for cap nut, max. | 3 Nm | Torque for cap nut, min. | 2 Nm |
| Torque for connecting adapter, max. | 2.5 Nm | Torque for connecting adapter, min. | 1.5 Nm |
| UL 94 flammability rating | V-2 | | |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 2.0 | EC000441 | ETIM 3.0 | EC000441 |
| UNSPSC | 30-21-18-01 | eClass 4.1 | 27-14-12-09 |
| eClass 5.1 | 27-14-91-09 | eClass 6.2 | 27-14-91-09 |
| eClass 7.1 | 27-14-91-09 | | |

Approvals

Approvals



ROHS Conform