

Han 48B-HBM-SL-CM



Image is for illustration purposes only. Please refer to product description.

Part number	09 30 048 0337
Specification	Han 48B-HBM-SL-CM
HARTING eCatalogue	https://b2b.harting.com/09300480337

Identification

Category	Hoods/Housings
Series of hoods/housings	Han® B
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	With metal cover incl. flat seal
Type	Low construction

Version

Size	48 B
Locking type	Single locking lever
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)



Pushing Performance
Since 1945

Material properties

Material (seal) NBR

Material (locking) Stainless steel

Specifications and approvals

CE Yes

Approvals DNV GL

Commercial data

Packaging size 1

Net weight 696.3 g

Country of origin Germany

European customs tariff number 85389099

GTIN 5713140165519

eCl@ss 27440202 Shell for industrial connectors