

Ratings

Voltage: 600 V
 Temperature: -40~105 °C
 Flammability: FT2

Conductor

Conductor count: 2
 Gauge: 22 AWG 0.13 mm²
 Material: tinned copper strands
 Strand size: $\phi 0.16 \times 17$
 Resistance at 20 °C: 59.4 Ω /km max

Insulator

Material: mPPE
 Color: red, black
 Diameter: $\phi 1.3 \pm 0.10$
 Average thickness: 0.26 mm
 Minimum thickness: 0.21 mm
 Resistance at 20 °C: 100 M Ω /km min

Shield

Type: foil
 Material: aluminum mylar
 Coverage: 100%



Outer jacket

Material: mPPE, 85A
 Color: black
 Diameter: $\phi 4.3 \pm 0.20$
 Average thickness: 0.8 mm
 Minimum thickness: 0.56 mm

Wire marking: E339579 UL AWM STYLE 21509 22 AWG 105°C 600V --- cUL AWM I A 105°C 600V FT2 TENSILITY

Bend radius

Minimum: 6 times diameter (25.8 mm)



Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	4/20/2020	Initial release	JC <small>Digitally signed by JC Date: 2020.04.20 13:34:15 -0700</small>	RoHS compliant	
			Verified:	Phthalate and halogen free	Size: Part number:
			AW <small>Digitally signed by AW Date: 2020.04.20 16:26:04 -0700</small>	Description:	A 30-01406
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Wire, 2C TS, 22 AWG, 21509, 600V, 105C, 4.3 mm, shielded, FT2, mPPE	Scale: 10:1
					Sheet 1 of 1

5

4

3

2

1