

# Product data sheet

Specifications



Harmony XVDLS, Monolithic tower light, plastic, red, Ø45, flashing, integral flash discharge tube 1 joule, 230 V AC

XVDLS6M4

## Main

|                                    |  |
|------------------------------------|--|
| Range of product                   | Harmony XVD Optimum  |
| Product or component type          | Complete miniature beacon  |
| Beacon or indicator bank unit type | Base unit direct fixing<br>Illuminated unit                              |
| Signalling type                    | Flashing   |
| Mounting diameter                  | 45 mm  |
| Component name                     | XVDLS  |
| Material                           | Glass reinforced polyamide: base unit<br>Polycarbonate: illuminated unit |
| Light source                       | Integral flash discharge tube, red                                       |
| Bulb type                          | Flash discharge tube   |
| [Us] rated supply voltage          | 230 V AC   |

## Complementary

|  |  |
|--|--|
| Connections - terminals                | Screw clamp terminals, <= 1 x 1.5 mm <sup>2</sup> with cable end |
| Cable entry                            | 1 entry tapped for Pg 7  |
| [Ui] rated insulation voltage          | 250 V conforming to IEC 60947-1                                  |
| Current consumption                    | < 25 mA AC   |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to IEC 60947-1                                   |
| Flash energy                           | 1 J  |
| CAD overall width                      | 45 mm  |
| CAD overall height                     | 104 mm   |
| CAD overall depth                      | 45 mm  |
| Terminals description ISO n°1          | (COM-1)PW<br>(GND)GROUND   |
| Product weight                         | 0.085 kg   |

## Environment

|                        |                  |
|------------------------|------------------|
| Product certifications | UL<br>CSA        |
| Standards              | EN/IEC 60947-5-1 |

|                                     |                                  |
|-------------------------------------|----------------------------------|
| Protective treatment                | TC                               |
| Ambient air temperature for storage | -40...70 °C                      |
| Electrical shock protection class   | Class II conforming to IEC 60536 |
| IP degree of protection             | IP40 conforming to IEC 60529     |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 5.6 cm   |
| Package 1 Width              | 5.6 cm   |
| Package 1 Length             | 11.2 cm  |
| Package 1 Weight             | 100.0 g  |
| Unit Type of Package 2       | S01      |
| Number of Units in Package 2 | 12       |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 15.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 1.407 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Illuminated Beacon

---


Dimensions



**Illuminated Beacon**

---

**Panel Cut-out for Direct Fixing**



**Recommended replacement(s)**