

# Han Ex 4A-QL Kit HCC-M20/HTE-M20



Part number	10 36 004 0011
Specification	Han Ex 4A-QL Kit HCC-M20/HTE-M20
HARTING eCatalogue	https://b2b.harting.com/10360040011

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Connector sets
Series	Han A <sup>®</sup>
Series of hoods/housings	Han <sup>®</sup> Ex
Element	Complete set

#### Version

Termination method	Han-Quick Lock <sup>®</sup> termination
Size	3 A
Number of contacts	4
PE contact	Yes
Version	Top entry
Cable entry	1x M20 1x M20
Locking type	Single locking lever
Field of application	Connectors for explosion hazardous environments

# **Technical characteristics**

Rated current	10 A
Rated voltage	90 V
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-20 +40 °C
Mating cycles	≥500

Page 1 / 3 | Creation date 2023-05-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Product data sheet 10 36 004 0011 Han Ex 4A-QL Kit HCC-M20/HTE-M20



## **Technical characteristics**

Degree of protection acc	to IEC 60529
--------------------------	--------------

IP67 with seal screw 09 20 000 9918

Material properties		
Material (insert)	Polycarbonate (PC)	
Material (hood/housing)	Zinc die-cast	
Surface (hood/housing)	Powder-coated	
Colour (hood/housing)	RAL 5015 (sky blue)	
Material (seal)	NBR	
Material (locking)	Stainless steel	
Material flammability class acc. to UL 94	V-0	
RoHS	compliant with exemption	
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight	
ELV status	compliant with exemption	
China RoHS	50	
REACH Annex XVII substances	Not contained	
REACH ANNEX XIV substances	Not contained	
REACH SVHC substances	Yes	
REACH SVHC substances	Lead	
California Proposition 65 substances	Yes	
California Proposition 65 substances	Lead Nickel Naphthalene	

## Specifications and approvals

	IEC 60664-1
acifications	IEC 61984
Specifications	IEC 60079-0
	EN 60079-11
Specifications	

# Commercial data

Packaging size	1
Net weight	210 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140163508

Page 2 / 3 | Creation date 2023-05-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Product data sheet 10 36 004 0011 Han Ex 4A-QL Kit HCC-M20/HTE-M20



Commercial data

eCl@ss

27440113 Rectangular connectors (set)

Page 3 / 3 | Creation date 2023-05-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany