

	1	2	3	4	5	6	7																																																																						
A									A																																																																				
B																B																																																													
C																C																																																													
D																D																																																													
E																E																																																													
F																F																																																													
G	RoHS compliant		<table border="1"> <tr> <td>Scale</td> <td>1:1</td> <td></td> <td></td> <td></td> <td></td> <td>Date</td> <td>Name</td> <td>Customer-No.</td> </tr> <tr> <td colspan="2">TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>30.05.2005</td> <td>Hellwig</td> </tr> <tr> <td>X.</td> <td>±X</td> <td>④</td> <td>add operating temp.</td> <td>05.05.2021</td> <td>Larsen</td> <td>Approved</td> <td>05.05.2021</td> <td>Larsen</td> </tr> <tr> <td>X.X</td> <td>±X</td> <td>③</td> <td>Update</td> <td>02.03.2012</td> <td>Schulz</td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±X</td> <td>②</td> <td>Update</td> <td>31.07.2009</td> <td>Rale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>X°</td> <td>±X</td> <td>①</td> <td>Drawn</td> <td>30.05.2005</td> <td>Hellwig</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="2" rowspan="2"> </td> <td>Drawing-No.</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>ASS 1317 CO</td> <td>rev04</td> </tr> </table>		Scale	1:1					Date	Name	Customer-No.	TOLERANCE						Drawn	30.05.2005	Hellwig	X.	±X	④	add operating temp.	05.05.2021	Larsen	Approved	05.05.2021	Larsen	X.X	±X	③	Update	02.03.2012	Schulz				X.XX	±X	②	Update	31.07.2009	Rale				X°	±X	①	Drawn	30.05.2005	Hellwig						Id.	Modification	Date	Name			Drawing-No.							ASS 1317 CO	rev04	<p>Material: AES Santoprene 111-TPE Operating temperature: -35°C ~ +105°C</p>	G
Scale	1:1					Date	Name	Customer-No.																																																																					
TOLERANCE						Drawn	30.05.2005	Hellwig																																																																					
X.	±X	④	add operating temp.	05.05.2021	Larsen	Approved	05.05.2021	Larsen																																																																					
X.X	±X	③	Update	02.03.2012	Schulz																																																																								
X.XX	±X	②	Update	31.07.2009	Rale																																																																								
X°	±X	①	Drawn	30.05.2005	Hellwig																																																																								
		Id.	Modification	Date	Name			Drawing-No.																																																																					
								ASS 1317 CO	rev04																																																																				
H								<table border="1"> <tr> <td>Replace</td> <td>Sheet</td> </tr> </table>	Replace	Sheet	H																																																																		
Replace	Sheet																																																																												
	1	2	3	4	5	6	7																																																																						