

C-FILTER D-SUB STANDARD

Solder cup – Precision machined contacts – For wire size AWG 20




RoHS compliant – CSA listed, File No.: LR 115000-1 – UL listed, File No.: E202784

DESCRIPTION


- Suitable for wire size **AWG 20**
- Mounting styles:
 - with through-hole, $\varnothing .118"/3$ mm
 - with 4-40 UNC or M3 threaded insert
- Quality class 3 (also available in quality class 1)
- Shell: Steel tin plated (brass tin plated on request)

SOCKET CONNECTOR




No. of pos.	A -0.76	B -0.25	C
09	31.19	16.46	25.00 $^{+0.12}_{-0.13}$
15	39.52	24.79	33.30 $^{+0.15}_{-0.10}$
25	53.42	38.50	47.04 ± 0.13
37	69.70	54.96	63.50 ± 0.13


Mounting style: Through-hole



Mounting style: Threaded insert




PLUG CONNECTOR




No. of pos.	A -0.76	B +0.25	C	D -0.3
09	31.19	16.79	25.00 $^{+0.12}_{-0.13}$	6.12
15	39.52	25.12	33.30 $^{+0.15}_{-0.10}$	6.12
25	53.42	38.84	47.04 ± 0.13	5.99
37	69.70	55.30	63.50 ± 0.13	5.99

Mounting style: Through-hole



Mounting style: Threaded insert



ORDER DATA

Capacitance 180 pF

SOCKET CONNECTOR

No. of pos.	Mounting style	Part Number
09	Through-hole	242 A 26740 X
15	Through-hole	242 A 26750 X
25	Through-hole	242 A 26760 X
37	Through-hole	242 A 26770 X
09	4-40 UNC Threaded insert	242 A 26900 X
15	4-40 UNC Threaded insert	242 A 26910 X
25	4-40 UNC Threaded insert	242 A 26920 X
37	4-40 UNC Threaded insert	242 A 26930 X
09	M3 Threaded insert	242 A 27060 X
15	M3 Threaded insert	242 A 27070 X
25	M3 Threaded insert	242 A 27080 X
37	M3 Threaded insert	242 A 27090 X

PLUG CONNECTOR

No. of pos.	Mounting style	Part Number
09	Through-hole	241 A 26840 X
15	Through-hole	241 A 26850 X
25	Through-hole	241 A 26860 X
37	Through-hole	241 A 26870 X
09	4-40 UNC Threaded insert	241 A 27000 X
15	4-40 UNC Threaded insert	241 A 27010 X
25	4-40 UNC Threaded insert	241 A 27020 X
37	4-40 UNC Threaded insert	241 A 27030 X
09	M3 Threaded insert	241 A 27160 X
15	M3 Threaded insert	241 A 27170 X
25	M3 Threaded insert	241 A 27180 X
37	M3 Threaded insert	241 A 27190 X

C-FILTER D-SUB STANDARD

Solder cup – Precision machined contacts – For wire size AWG 20

ORDER DATA

Capacitance 370 pF			
SOCKET CONNECTOR			PLUG CONNECTOR
No. of pos.	Mounting style	Part Number	Part Number
09	Through-hole	242 A 26780 X	241 A 26880 X
15	Through-hole	242 A 26790 X	241 A 26890 X
25	Through-hole	242 A 26800 X	241 A 26900 X
37	Through-hole	242 A 26810 X	241 A 26910 X
09	4-40 UNC Threaded insert	242 A 26940 X	241 A 27040 X
15	4-40 UNC Threaded insert	242 A 26950 X	241 A 27050 X
25	4-40 UNC Threaded insert	242 A 26960 X	241 A 27060 X
37	4-40 UNC Threaded insert	242 A 26970 X	241 A 27070 X
09	M3 Threaded insert	242 A 27100 X	241 A 27200 X
15	M3 Threaded insert	242 A 27110 X	241 A 27210 X
25	M3 Threaded insert	242 A 27120 X	241 A 27220 X
37	M3 Threaded insert	242 A 27130 X	241 A 27230 X

Capacitance 830 pF			
SOCKET CONNECTOR			PLUG CONNECTOR
No. of pos.	Mounting style	Part Number	Part Number
09	Through-hole	242 A 26820 X	241 A 26920 X
15	Through-hole	242 A 26830 X	241 A 26930 X
25	Through-hole	242 A 26840 X	241 A 26940 X
37	Through-hole	242 A 26850 X	241 A 26950 X
09	4-40 UNC Threaded insert	242 A 26980 X	241 A 27080 X
15	4-40 UNC Threaded insert	242 A 26990 X	241 A 27090 X
25	4-40 UNC Threaded insert	242 A 27000 X	241 A 27100 X
37	4-40 UNC Threaded insert	242 A 27010 X	241 A 27110 X
09	M3 Threaded insert	242 A 27140 X	241 A 27240 X
15	M3 Threaded insert	242 A 27150 X	241 A 27250 X
25	M3 Threaded insert	242 A 27160 X	241 A 27260 X
37	M3 Threaded insert	242 A 27170 X	241 A 27270 X

Capacitance 1300 pF			
SOCKET CONNECTOR			PLUG CONNECTOR
No. of pos.	Mounting style	Part Number	Part Number
09	Through-hole	242 A 26860 X	241 A 26960 X
15	Through-hole	242 A 26870 X	241 A 26970 X
25	Through-hole	242 A 26880 X	241 A 26980 X
37	Through-hole	242 A 26890 X	241 A 26990 X
09	4-40 UNC Threaded insert	242 A 27020 X	241 A 27120 X
15	4-40 UNC Threaded insert	242 A 27030 X	241 A 27130 X
25	4-40 UNC Threaded insert	242 A 27040 X	241 A 27140 X
37	4-40 UNC Threaded insert	242 A 27050 X	241 A 27150 X
09	M3 Threaded insert	242 A 27180 X	241 A 27280 X
15	M3 Threaded insert	242 A 27190 X	241 A 27290 X
25	M3 Threaded insert	242 A 27200 X	241 A 27300 X
37	M3 Threaded insert	242 A 27210 X	241 A 27310 X