




Powering Business Worldwide

1000 Eaton Boulevard
Cleveland, OH 44122
United States

Eaton Internal Replacement Battery Cartridge (RBC) for 5P750R and 5P850GR 5P UPS Systems

MODEL NUMBER: 744-A2220



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 5P UPS system.

Features

UPS Replacement Battery Cartridge for Select Eaton 5P UPS Systems

This UPS backup battery replacement is compatible with Eaton's 5P750R and 5P850GR UPS systems. Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A2220 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A2220 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your 5P UPS system.

Specifications

OVERVIEW	
UPC Code	786689367268
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
Battery Replacement Description	Re-use existing wiring harness
Hot Swap Battery	Yes

Highlights

- Replacement battery backup for Eaton 5P750R and 5P850GR 5P UPS systems
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships pre-wired and ready for immediate installation to prevent downtime

System Requirements

Compatible only with Eaton's 5P750R and 5P850GR UPS systems

Package Includes

744-A2220 Internal Replacement Battery Cartridge



Powering Business Worldwide

1000 Eaton Boulevard
Cleveland, OH 44122
United States

PHYSICAL	
Unit Dimensions (hwd / in.)	1.430 x 12.630 x 8.190
Unit Weight (lbs.)	12.1
Unit Weight (kg)	5.49
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
APPLICATIONS	
Used With	5P750R, 5P850GR
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed; cUL Listed
Product Compliance	RoHS; FCC (USA); Trade Agreements Act (TAA)



Powering Business Worldwide

© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.