



- 1 CONTINUOUS STRIP ON REELS WITH TERMINALS LOCATED ON 5.59±0.08 [.220±.003] CENTERS. SLOTS ACCEPTS EITHER A SINGLE OR DOUBLE MAGNET WIRE OF THE SAME SIZE AND TYPE COPPER RANGE: 0.32-0.51mm [#28-#24] AWG
- 2 POKE-IN ACCEPTS A 0.5-0.8mm<sup>2</sup> [#20-#18] AWG SOLID OR FUSED STRANDED LEAD WIRE.
- 3 AFTER INSERTION INTO PLASTIC HOLDER TAB PORTION MUST BE BENT OVER 45° TO 90° OR POTTED-IN TO PREVENT PULL-OUT WHEN MATING RECEPTACLE IS DISCONNECTED.
- 4

LOC	DIST	REVISIONS	DATE	APPD
AF	50			
P	F	ZONE	LTR	
		J1	REVISE PER ECR-12-022060	28DEC12
				CX/LL

OBSOLETE -63062-1- PART NO

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN mm [INCHES] TOLERANCES ON : 2. PLC DEC ± 0.25 [.010] 3. PLC DEC ± _ _ ANGLES ± _ _ MATERIAL 4M PRE-MILLED BRASS	DR 9/MAR/95 R.GRZYBOWSKI	NAME <b>AMP</b> AMP Incorporated Harrisburg, PA 17105-3608
FINISH 0.002032 [.000080] MIN TIN PLATE	CHK 16/MAR/95 M.S.FEHER	TERMINAL, TAB, POKE-IN / 2.79 [.110] FASTON,™ COMBINATION, MAG-MATE™
4M PRE-MILLED BRASS	APPD 16/MAR/95 NELSON E. NEFF	SIZE CAGE CODE DRAWING NO
PRODUCT SPEC 108-2012	APPD 16/MAR/95 TERRY L. SHUTTER	SCALE 10:1
APPLICATION SPEC 114-2046	WEIGHT	SHEET 10F 1

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.