


HT06BW104KN

Obsolete

HP LDD Indust X7R HT200C, Ceramic, 0.1 uF, 10%, 50 VDC, X7R, Commercial, High Temperature, Lead Spacing = $5.08 \, \text{mm}$



Click here for the 3D model.

Dimensions	,
L	7.62mm MAX
Н	7.62mm MAX
Т	3.81mm MAX
S	5.08mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

DI		C	_:.c:_	
наска	Tellate	SDE		ations
	. 5 5	~~~	~	~

Packaging Waffle, Tray

General Information			
HP LDD Indust X7R HT200C			
Radial			
Commercial, High Temperature			
LDD High Temperature 200C			
No			
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.			
Nickel			
No			

Specifications	
Capacitance	0.1 uF
Capacitance Tolerance	10%
Voltage DC	50 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	X7R

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.