# Product data sheet Characteristics

# 9001KZC297 SECURITY CONTROL STATION 600VAC 15A



#### Main

Range of Product	Harmony 9001K
Product or Component Type	Security control station
Device short name	9001KY
Lock type	Complete with core, 6 tumbler pins

#### Complementary

Size	30 mm	
Enclosure/cubicle description	Flush mounting	
Enclosure Material	Stainless Steel	
Type of installation	Indoor	
Control station composition	1 key selector switch, spring return OPEN-CLOSE 1 push-button STOP	
Type of Keylock	Best	
Key withdrawal position	Center	
Connections - terminals	Screw clamp terminal	
[Ue] rated operational voltage	300 V	
[le] rated operational current AC	15 A	
Product Weight	4.98 lb(US) (2.26 kg)	

#### Environment

NEMA Degree of Protection	NEMA 1
Environmental characteristic	Waterproof
Product Certifications	UL Listed CSA CE
Ambient Air Temperature for Operation	-13140 °F (-2560 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)

#### Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	785901853275
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.70 in (32.258 cm)
Package 1 Width	5.00 in (12.7 cm)
Package 1 Length	32.26 in (81.935 cm)
Package 1 Weight	5.00 lb(US) (2.268 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration
Mercury free	Yes
China RoHS Regulation	der China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

#### Contractual warranty

Contraction Warranty		
Warranty	18 months	