

## [Oscilloscope] Specifications

Model	HDS242	HDS272	HDS242S	HDS272S
Bandwidth	40MHz	70MHz	40MHz	70MHz
Channels	2-CH Oscilloscope		2-CH Oscilloscope+1-CH Generator	
Sample Rate	250MSa/s			
Acquisition Model	Normal, Peak detect			
Record Length	8K			
Display	3.5-inch LCD			
Waveform Refresh Rate	10,000 wfms/s			
Input Coupling	DC, AC, and Ground			
Input Impedance	1 MΩ±2%, in parallel with 16pF±10pF			
Probe Attenuation Factors	1X, 10X, 100X, 1000X, 10000X			
Max. input Voltage	400V (DC+AC, PK-PK, 1MΩ input impedance) (10:1 probe attenuation)			
Bandwidth Limit (typical)	20MHz			
Horizontal Scale	5ns/div - 1000s/div, step by 1 - 2 - 5			
Vertical Sensitivity	10mV/div - 10V/div			
Vertical Resolution	8 bits			
Trigger Type	Edge			
Trigger Modes	Auto, Normal, single			
Automatic Measurement	Period, Frequency, Mean, PK-PK, Max, Min			
Cursor Measurement	ΔV, ΔT, ΔT&ΔV between cursors			
Communication Interface	USB Type-C			

## [Multimeter] Specifications (Standard)

Max. Resolution	20,000 counts
Testing Mode	Voltage, Current, Resistance, Capacitance, Diode ,and Continuity test
Input Impedance	10MΩ
Max Input Voltage	AC 750V, DC 1000V
Max Input Current	DC : 10A AC : 10A
Diode	0 - 2V

## [Waveform Generator] Specifications (Only for HDS242S & HDS272S)

Frequency Output	Sine	0.1Hz - 25MHz
	Square	0.1Hz - 5MHz
	Ramp	0.1Hz - 1MHz
	Pulse	0.1Hz - 5MHz
	Arbitrary	0.1Hz - 5MHz
Sampling Rate	125MSa/s	
Channel	1-CH	
Amplitude Range	20 mVpp - 5 Vpp	
Waveform Length	8K	
Vertical Resolution	14bits	
Output Impedance	50Ω	