

6

5

4

3

2

1

PART NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1300508029	ENV3135M010	3' 3" +2.19"/-0" [ 1M +55.6/-0 mm ]

NOTES:

1) MATERIAL: SEE TABLE

2) FINISHES: SEE TABLE

3) CABLE: #24/8 SHIELDED TWISTED PAIR, PUR

4) ELECTRICAL DATA:  
ACCORDING TO CAT5e ETHERNET STANDARD  
MAX. VOLTAGE: 30V  
MAX. CURRENT 1.5A

5) ENVIRONMENTAL:  
PROTECTION IP67  
TEMPERATURE RANGE: -20°C TO +80°C

6) WRAP LABEL IS MARKED WITH P/N & DATE CODE.

7) ASSEMBLY IS RoHS COMPLIANT.

WIRE LIST	
PIN #	COLOR
1	WHITE/ORANGE
2	ORANGE
3	WHITE/GREEN
4	BLUE
5	WHITE/BLUE
6	GREEN
7	WHITE/BROWN
8	BROWN
GND	DRAIN WIRE

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
6	1	RJ45 PLUG	POLYCARBONATE	CLEAR
5	1	COUPLING NUT	ABS	BLACK
4	1	LABEL	PLASTIC FILM	BLACK/YELLOW
3	1	RJ45 PLUG	POLYCARBONATE	CLEAR
2	1	BOOT	PVC	BLACK
1	1	ETHERNET CABLE-CAT5E	PUR JACKET	BLACK

<b>RELEASE DRAWING</b> EC NO: WNA2010-0442 DRWN: TVICKERS 2010/01/18 CHKD: B.WOODMA APPR: DTTITUS 2010/01/19	<b>QUALITY SYMBOLS</b> $\nabla = 0$ $\nabla C = 0$															
	<b>GENERAL TOLERANCES (UNLESS SPECIFIED)</b> <table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>±---</td> <td>±---</td> </tr> <tr> <td>3 PLACES</td> <td>±---</td> <td>±.005</td> </tr> <tr> <td>2 PLACES</td> <td>±0.13</td> <td>±.010</td> </tr> <tr> <td>1 PLACE</td> <td>±0.25</td> <td>±.020</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	±---	±---	3 PLACES	±---	±.005	2 PLACES	±0.13	±.010	1 PLACE	±0.25	±.020
		mm	INCH													
	4 PLACES	±---	±---													
3 PLACES	±---	±.005														
2 PLACES	±0.13	±.010														
1 PLACE	±0.25	±.020														
<b>ANGULAR ±1/2°</b> <b>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</b>																
<b>SIZE A</b>																

<b>THIRD ANGLE PROJECTION</b>
<b>ETHERNET MMJ IND./RJ45 568-B SHIELD ASSEMBLY PUR STRANDED CABLE</b>
<b>MOLEX INCORPORATED</b>
<b>SD-130050-022</b>
<b>1 OF 1</b>

<b>GENERAL TOLERANCES (UNLESS SPECIFIED)</b> <table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>±---</td> <td>±---</td> </tr> <tr> <td>3 PLACES</td> <td>±---</td> <td>±.005</td> </tr> <tr> <td>2 PLACES</td> <td>±0.13</td> <td>±.010</td> </tr> <tr> <td>1 PLACE</td> <td>±0.25</td> <td>±.020</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	±---	±---	3 PLACES	±---	±.005	2 PLACES	±0.13	±.010	1 PLACE	±0.25	±.020
	mm	INCH													
4 PLACES	±---	±---													
3 PLACES	±---	±.005													
2 PLACES	±0.13	±.010													
1 PLACE	±0.25	±.020													
<b>ANGULAR ±1/2°</b> <b>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</b>															
<b>SIZE A</b>															

<b>THIRD ANGLE PROJECTION</b>
<b>ETHERNET MMJ IND./RJ45 568-B SHIELD ASSEMBLY PUR STRANDED CABLE</b>
<b>MOLEX INCORPORATED</b>
<b>SD-130050-022</b>
<b>1 OF 1</b>

6

5

4

3

2

1