

N-channel 40 V, 2.2 mΩ typ., 32 A STripFET™ F5 Power MOSFET in a PowerFLAT™ 5x6 package

Datasheet - production data





Figure 1: Internal schematic diagram



Features

Order code	V _{DS}	R _{DS(on)} max.	I _D
STL140N4LLF5	40 V	2.75 mΩ	32 A

- Low on-resistance R_{DS(on)}
- High avalanche ruggedness
- Low gate drive power loss

Applications

- Switching applications

Description

This N-channel Power MOSFET is developed using the STripFET™ F5 technology and has been optimized to achieve very low on-state resistance, contributing to a FoM that is among the best in its class.

Table 1: Device summary

Order code	Marking	Package	Packing
STL140N4LLF5	140N4LF5	PowerFLAT™ 5x6	Tape and reel

Contents

1	Electrical ratings	3
2	Electrical characteristics	4
2.1	Electrical characteristics (curves)	6
3	Test circuits	8
4	Package information	9
4.1	PowerFLAT™ 5x6 type C package information	9
4.2	PowerFLAT™ 5x6 packing information	11
5	Revision history	13

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	40	V
V_{GS}	Gate-source voltage	± 22	V
$I_D^{(1)}$	Drain current (continuous) at $T_C = 25^\circ\text{C}$	140	A
$I_D^{(1)}$	Drain current (continuous) at $T_C = 100^\circ\text{C}$	88	A
$I_D^{(2)}$	Drain current (continuous) at $T_{\text{pcb}} = 25^\circ\text{C}$	32	A
$I_D^{(2)}$	Drain current (continuous) at $T_{\text{pcb}} = 100^\circ\text{C}$	20	A
$I_{DM}^{(3)}$	Drain current (pulsed)	128	A
$P_{\text{TOT}}^{(1)}$	Total dissipation at $T_C = 25^\circ\text{C}$	80	W
$P_{\text{TOT}}^{(2)}$	Total dissipation at $T_{\text{pcb}} = 25^\circ\text{C}$	4	W
T_{stg}	Storage temperature range	$-55 \text{ to } 150$	$^\circ\text{C}$
T_j	Operating junction temperature range		

Notes:(1) This value is rated according to $R_{\text{thj-case}}$.(2) This value is rated according to $R_{\text{thj-pcb}}$.

(3) Pulse width limited by safe operating area.

Table 3: Thermal data

Symbol	Parameter	Value	Unit
$R_{\text{thj-case}}$	Thermal resistance junction-case	1.56	$^\circ\text{C/W}$
$R_{\text{thj-pcb}}^{(1)}$	Thermal resistance junction-pcb	31.3	$^\circ\text{C/W}$

Notes:(1) When mounted on FR-4 board of 1 inch², 2 oz Cu t < 10 sec

Table 4: Avalanche characteristics

Symbol	Parameter	Value	Unit
I_{AV}	Not-repetitive avalanche current, (pulse width limited by $T_{j\max}$)	16	A
E_{AS}	Single pulse avalanche energy (starting $T_j = 25^\circ\text{C}$, $I_D = I_{AV}$, $V_{DD} = 24\text{ V}$)	300	mJ

2 Electrical characteristics

$T_C = 25^\circ\text{C}$ unless otherwise specified

Table 5: On/off-state

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	40			V
I_{DSS}	Zero gate voltage drain current	$V_{GS} = 0 \text{ V}, V_{DS} = 40 \text{ V}$			1	μA
		$V_{GS} = 0 \text{ V}, V_{DS} = 40 \text{ V}, T_C = 125^\circ\text{C}$ (1)			10	μA
I_{GSS}	Gate body leakage current	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 22 \text{ V}$			± 100	μA
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	1			V
$R_{DS(on)}$	Static drain-source on-resistance	$V_{GS} = 10 \text{ V}, I_D = 16 \text{ A}$		2.2	2.75	$\text{m}\Omega$
		$V_{GS} = 4.5 \text{ V}, I_D = 16 \text{ A}$		2.4	3.1	$\text{m}\Omega$

Notes:

(1)Defined by design, not subject to production test.

Table 6: Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	$V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}, V_{GS} = 0 \text{ V}$	-	5900	-	pF
C_{oss}	Output capacitance		-	870	-	pF
C_{rss}	Reverse transfer capacitance		-	130	-	pF
Q_g	Total gate charge	$V_{DD} = 15 \text{ V}, I_D = 32 \text{ A}$ $V_{GS} = 0 \text{ to } 4.5 \text{ V}$, see (Figure 14: "Test circuit for gate charge behavior")	-	45	-	nC
Q_{gs}	Gate-source charge		-	14	-	nC
Q_{gd}	Gate-drain charge		-	17	-	nC
R_G	Gate input resistance	$f=1 \text{ MHz},$ gate DC bias = 0 V, test signal level = 20 mV, $I_D = 0 \text{ A}$	-	1.2	-	Ω

Table 7: Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 15 \text{ V}, I_D = 16 \text{ A}, R_G = 4.7 \Omega$ $V_{GS} = 10 \text{ V}$, (see Figure 13: "Test circuit for resistive load switching times" and Figure 18: "Switching time waveform")	-	19	-	ns
t_r	Rise time		-	29	-	ns
$t_{d(off)}$	Turn-off delay time		-	90	-	ns
t_f	Fall time		-	21	-	ns

Table 8: Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Forward on voltage		-		32	A
$I_{SDM}^{(1)}$	Source-drain current (pulsed)		-		128	A
$V_{SD}^{(2)}$	Forward on voltage	$I_{SD} = 32 \text{ A}, V_{GS}=0 \text{ V}$	-		1.1	V
t_{rr}	Reverse recovery time	$I_{SD} = 32 \text{ A}, \text{di/dt} = 100 \text{ A}/\mu\text{s}, V_{DD}= 25 \text{ V}$ (see <i>Figure 15: "Test circuit for inductive load switching and diode recovery times"</i>)	-	44		ns
Q_{rr}	Reverse recovery charge		-	57		nC
I_{RRM}	Reverse recovery current		-	2.6		A

Notes:

(1)Pulse width limited by safe operating area.

(2)Pulsed: pulse duration=300μs, duty cycle 1.5%.

2.1 Electrical characteristics (curves)












Figure 2: Safe operating area**Figure 3: Thermal impedance****Figure 4: Output characteristics****Figure 5: Transfer characteristics****Figure 6: Gate charge vs gate-source voltage****Figure 7: Static drain-source on-resistance**

Figure 8: Capacitance variations**Figure 9: Normalized gate threshold voltage vs temperature****Figure 10: Normalized on-resistance vs temperature****Figure 11: Normalized $V_{(BR)DSS}$ vs temperature****Figure 12: Source- drain diode forward characteristics**

3 Test circuits

Figure 13: Test circuit for resistive load switching times




Figure 14: Test circuit for gate charge behavior




Figure 15: Test circuit for inductive load switching and diode recovery times




Figure 16: Unclamped inductive load test circuit




Figure 17: Unclamped inductive waveform





Figure 18: Switching time waveform



4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com.
ECOPACK® is an ST trademark.

4.1 PowerFLAT™ 5x6 type C package information

Figure 19: PowerFLAT™ 5x6 type C package outline





Table 9: PowerFLAT™ 5x6 type C package mechanical data


Dim.	mm		
	Min.	Typ.	Max.
A	0.80		1.00
A1	0.02		0.05
A2		0.25	
b	0.30		0.50
C	5.80	6.00	6.20
D	5.00	5.20	5.40
D2	4.15		4.45
D3	4.05	4.20	4.35
D4	4.80	5.00	5.20
D5	0.25	0.40	0.55
D6	0.15	0.30	0.45
e		1.27	
E	5.95	6.15	6.35
E2	3.50		3.70
E3	2.35		2.55
E4	0.40		0.60
E5	0.08		0.28
E6	0.20	0.325	0.45
E7	0.75	0.90	1.05
K	1.05		1.35
L	0.725		1.025
L1	0.05	0.15	0.25
θ	0°		12°

Figure 20: PowerFLAT™ 5x6 recommended footprint (dimensions are in mm)



4.2 PowerFLAT™ 5x6 packing information

Figure 21: PowerFLAT™ 5x6 tape (dimensions are in mm)



8234350_Tape_rev_C

Figure 22: PowerFLAT™ 5x6 package orientation in carrier tape





Figure 23: PowerFLAT™ 5x6 reel



5 Revision history

Table 10: Document revision history

Date	Revision	Changes
03-Jun-2010	1	First release.
29-Apr-2011	2	Document status promoted from preliminary data to datasheet.
10-Nov-2011	3	Section 4: Package mechanical data has been updated. Minor text changes.
08-Aug-2017	4	Modified Table 1: "Device summary" . Updated Section 5: "Package information" . Minor text changes.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved