



NOTES

- 1 材料 : TABLE 1参照
MATERIAL : SEE TABLE 1
- 2 極数 = 偶数に適用
APPLY FOR CIRCUIT SIZE =EVEN
- 3. 適合製品及び各種仕様書は下記参照のこと
REFER TO BELOW TABLE ABOUT RELATED PRODUCTS
AND VARIOUS SPECIFICATIONS.

適合製品及び各種仕様書
APPCABLE PRODUCTS AND VARIOUS SPECIFICATIONS

適合圧着端子 APPLICABLE TERMINAL	PART NUMBER 2040175021	WIRE SIZE AWG #28-#30
適合嵌合相手 MATE WITH	212134 SERIES	
製品仕様書 PRODUCT SPECIFICATION	2121320000-PS/PS/000	
梱包仕様書 PACKING SPECIFICATION	2121329200-SPK/PS/000	
コネクタ取扱説明書 APPLICATION SPECIFICATION	2166940000-AS/PS/000	

製品嵌合図は嵌合相手図面参照のこと
MATING VIEW: REFER TO "MATE WITH" PART DRAWING.

5	6.2	2121320006	6
4	5.2	2121320005	5
3	4.2	2121320004	4
2	3.2	2121320003	3
1	2.2	2121320002	2
B	A	オーダー番号 ORDER No 梱包形態 : ポリ袋 PACKAGING POLYBAG	極数 CIRCUIT SIZE

1 TABLE 1

部品 PART	材質 MATERIAL
ハウジング HOUSING	ポリアミド(PA)ガラス入り, UL94-V0, 色 : 黒 POLYAMIDE (PA) GLASS FILLED, UL94-V0, COLOR : BLACK

DOCUMENT STATUS	P1	RELEASE DATE	2020/09/17	06:07:17
-----------------	----	--------------	------------	----------

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS mm	SCALE NTS	CURRENT REV DESC:		molex			
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 643659					
ANGULAR TOL	± 3.0 °	DRWN: SNAKAMURA08 2019/05/28		PRODUCT CUSTOMER DRAWING			
4 PLACES	± 0.2	CHK'D: SAKIYAMA 2020/09/17		DOCUMENT NUMBER			
3 PLACES	± 0.2	APPR: KOMURAKAMI 2020/09/17		2121320000-SD			
2 PLACES	± 0.2	INITIAL REVISION:		DOC TYPE			
1 PLACE	± 0.2	DRWN: SNAKAMURA08 2019/05/28		PSD			
0 PLACES	± 0.2	APPR: KOMURAKAMI 2020/09/17		000			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES	
		A3-SIZE		212132		SHEET NUMBER	
		GENERAL		1 OF 1			