



PIN ASSINGNMENT

P1	P2	
A4, A9, B4, B9	Red (VBUS)	A4, A9, B4, B9
A5	Blue (CC)	A5
A6	White (D-)	A6
A7	Green (D+)	A7
A1, A12, B1, B12	Black (GND)	A1, A12, B1, B12
SHELL	Braid	SHELL

一、Electrical charactor:

- (1) 100% Open & Short Testing
- (2) Withstanding Voltage:DC 300V, 0.01s
- (3) Insulation impedance: $\cong 10M\Omega$
- (4) Conduction impedance: $\leq 0.4\Omega$

二、Rated voltage:5V, Current:3A
Rated voltage:9V, Current:2A

5	ZTPE-101C60	MOLDED	TPE插頭料, 黑色, 85A (45P), UL94-HB, 符合ROHS+HF	N/A	KG
4	PLASTIC-086	MOLDED	LD-PE, 透明	N/A	KG
3	ZPC-U31-B-042-01	SHIELD	TYPE C EMI Shell, SUS304, T=0.25mm, 鍍銀, (L=13.90*H3.60*W9.00), 帶柳爪.	2	PC
2	ZPC-U31-B-042	CONN	TYPE C/M, 24pin, pin針鍍金, 黑色膠芯, 外殼鍍銀, 一體拉伸式, 超薄款	2	PC
1	C000023L11L-4C	CABLE	USB2.0 30AWG/2C+30AWG/1C+23AWG/1C+F+EAB OD:3.5mmTPE 黑色	0.15	M
ITEM	PART No.	NAME	DESCRIPTION	Q' TY	UNIT

MATERIAL SPECIFICATION

△4	△3	△2	△1	DRAWN BY	CHECKED BY	APPROVED BY	CONFIRMED BY	DESCRIPTION	瀚荃股份有限公司 CviLux Corporation		CUST. CODE
				WANG	WANG	KENY	KENY	TYPE CM TO CM Cable ASSY	DRAWING No.	CviLux P/N	CUSTOMER P/N
SYM	NAME	DATE	REVISIONS	2021/4/12	2021/4/12	2021/4/12	2021/4/12	SHEET: 1 OF 1	D000071A	DH-20UE0062-NH	