



RATED VOLTAGE: 120 VAC, 60 Hz
 ROTATION: CCW
 NO LOAD SPEED: 2.2 RPM
 NO LOAD CURRENT: 0.54 A

LOADED SPEED @ 90 IN-LB: 2.0 RPM
 LOADED CURRENT @ 90 IN-LB: 0.55 A
 STALL TORQUE: 200 IN-LB
 STALL CURRENT: 0.69 A

THERMALLY PROTECTED, PER UL E92971, CSA 48508

I/WE CERTIFY THAT SAMPLES OF THIS MOTOR HAVE BEEN FULLY TESTED BY THE UNDERSIGNED AND THAT ALL SPECIFICATIONS HAVE BEEN REVIEWED FOR PRODUCTION. MULTIPRODUCTS COMPANY, INC. IS NOT RESPONSIBLE FOR MOTORS THAT FAIL IN THE FIELD DUE TO INSUFFICIENT TESTING OF THE SAMPLE MOTORS. I/WE AGREE TO PROVIDE MULTIPRODUCTS COMPANY, INC. WITH CURRENT DRAWINGS AND IN-HOUSE TEST PROCEDURES AS THEY BECOME AVAILABLE. ANY CHANGES THAT I/WE MAY MAKE WHICH OCCUR AFTER THE DATE SHOWN ARE SUBJECT TO REVIEW AND MAY AFFECT UNIT PRICE AND/OR DELIVERY DATES.

B	REDRAWN, UPDATED PERF. INFO, OVERALL LENGTH INCLUDES ROT. SHAFT	1/19/2015	3168
A	ADDED REF. DIM. TO REFLECT SHORT LEGS FOR COIL MOUNT	9/28/2009	2883
REV.	DESCRIPTION	DATE	ECO#

TOLERANCES

X.XX : ±.010
 X.XXX : ±.005
 FRACTION : ±1/64
 ANGLE : ±2°

UNLESS OTHERWISE SPECIFIED



MULTI PRODUCTS
 Company, Inc.

PART NAME/DESCRIPTION: **MULTIPRODUCTS**

DRAWN BY: PJ DATE: 12/6/2005 SCALE: 0.75:1 MATERIAL: -

CHK'D BY: - DATE: - PART NUMBER:

APPR'D BY: - DATE: -

MOD-UL52-9902A

SIGNATURE _____ PRINT NAME _____ DATE _____
 IN ORDER TO BEGIN PRODUCTION, MULTIPRODUCTS COMPANY, INC. MUST HAVE SIGNED APPROVAL.