

**MI8DO-S SUB D15S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Specific adapter to be connected to the MICROSERIE RELAYS using a 10-pole flat-cable connector or 15-pole Sub-D connector.

**General ordering data**

Type	MI8DO-S SUB D15S
Order No.	<a href="#">8773550000</a>
Version	IEC 60603/DIN41612 plug-in connectors, Screw connection
GTIN (EAN)	4032248442089
Qty.	1 pc(s).

## MI8DO-S SUB D15S

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Length	48 mm	Width	59 mm
Height	53 mm	Net weight	89 g

### Temperatures

Operating temperature	0...+55°C	Ambient temperature	0 °C...+55 °C
Storage temperature	-20...+85 °C		

### Connection data

Connection on control side	IEC 60603/DIN41612 plug-in connectors	Number of poles (control side)	25-pole plug
Supply voltage	24 V DC	Supply plug-in connectors	TOP 1.5GS2/180

### Ratings data

Operating voltage	30 V UC	Max. current per channel	0.5 A
Total operating current	2 A		

### Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

### Supply connection

Type of connection	Screw connection	Clamping range, min.	2.5 mm <sup>2</sup>
Clamping range, max.	0.13 mm <sup>2</sup>	Solid, min. H05(07) V-U	2.5 mm <sup>2</sup>
Solid, max. H05(07) V-U	0.5 mm <sup>2</sup>	Flexible, min. H05(07) V-K	2.5 mm <sup>2</sup>
Flexible, max. H05(07) V-K	0.5 mm <sup>2</sup>	Flexible with sleeve, max.	0.5 mm <sup>2</sup>
Flexible with sleeve, min.	2.5 mm <sup>2</sup>	Ferrule with plastic collar, max.	0.5 mm <sup>2</sup>
Wire cross-section, min. AWG	AWG 14	Wire cross-section, max. AWG	AWG 26
Tightening torque, min.	0.4 Nm	Tightening torque, max.	0.5 Nm
Stripping length	10 mm		

### Classifications

ETIM 3.0	EC001421	UNSPSC	30-21-18-01
eClass 5.1	27-24-22-02	eClass 6.2	27-24-22-02
eClass 7.1	27-24-22-02		

### Product information

Descriptive text ordering data	MI8DO-S = screw connection MI8DO-Z = tension clamp connection
--------------------------------	--

**Data sheet**

**MI8DO-S SUB D15S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Approvals**

Approvals



ROHS

Conform

**Downloads**

Declaration of Conformity

[K274\\_10\\_04.pdf](#)

**Data sheet****MI8DO-S SUB D15S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**