

“Stay Connected” with



HEYware Products

a PennEngineering® Company



- Smooth, radiused edges ensure that Nytyes won't cut into the cable's insulation—or the installer's hand.
- One-piece design reduces cost and installation time.
- Nytyes feature a bent tip for ease of pickup and insertion around small bundles. V-shaped raised ridges on the tip provide a sure grip.
- Close, evenly spaced teeth permit fine adjustment—from .025" (0,6 mm) on the smallest Nytyes to .063" (1,6 mm) on the largest.
- Standard UV Black Nytyes are available in 100 packs; add -P to Part No.; eg. 13140B-P
- Compliant with MS3367 and MIL-S-23190E

Heyco® Nytye® Nylon Cable Ties


PART SPECIFICATIONS				PART NO.		DESCRIPTION	PART DIMENSIONS			
Tensile Strength		Max. Bundle Diameter		Natural	UV Black		A Length		B Width	
Lbs.	N	in.	mm.			in.	mm.	in.	mm.	
Miniature										
18	80	.63	16,0	13100	13100B	NT-18-031	3.15	80	.10	2,5
		.87	22,0	13102	13102B	NT-18-039	3.94	100		
		1.18	30,0	13105	13105B	NT-18-047	4.72	120		
		1.38	35,0	13107	13107B	NT-18-059	5.91	150		
		1.57	40,0	13108	13108B	NT-18-063	6.30	160		
		2.36	60,0	13111	13111B	NT-18-078	7.87	200		
Intermediate										
40	178	.87	22,0	13120	13120B	NT-40-039	3.94	100	.14	3,6
		1.18	30,0	13121	13121B	NT-40-047	4.72	120		
		1.30	33,0	13122	13122B	NT-40-055	5.51	140		
		1.38	35,0	13123	13123B	NT-40-059	5.91	150		
		1.65	42,0	13124	13124B	NT-40-070	7.09	180		
		1.97	50,0	13126	13126B	NT-40-078	7.87	200		
		2.56	65,0	13128	13128B	NT-40-099	9.92	252		
		3.15	80,0	13129	13129B	NT-40-110	11.02	280		
		3.35	85,0	13130	13130B	NT-40-118	11.81	300		
		4.02	102,0	13134	13134B	NT-40-145	14.57	370		
Standard										
50	222	.94	24,0	13140	13140B	NT-50-047	4.72	120	.19	4,8
		1.57	40,0	13142	13142B	NT-50-063	6.30	160		
		1.65	42,0	13143	13143B	NT-50-072	7.20	183		
		1.97	50,0	13145	13145B	NT-50-078	7.87	200		
		2.56	65,0	13147	13147B	NT-50-098	9.84	250		
		2.76	70,0	13149	13149B	NT-50-110	11.02	280		
		3.23	82,0	13151	13151B	NT-50-118	11.81	300		
		3.54	90,0	13153	13153B	NT-50-137	13.78	350		
		4.02	102,0	13155	13155B	NT-50-145	14.57	370		
		4.13	105,0	13156	13156B	NT-50-157	15.75	400		
		5.12	130,0	13158	13158B	NT-50-177	17.72	450		
		5.91	150,0	13160	13160B	NT-50-196	19.68	500		

Heyco® Cable Tie Tensioning Tool



Part No. 0998 (for Nylon) and **0996** (for Stainless Steel) fits all standard duty Nytyes. Metal construction, has three tension settings, and automatically trims excess.

Standard colors natural and UV Black. Consult Heyco for heat-stabilized material and colors. Standard UV Black Nytyes available in 100 packs; add -P to Part No.; eg. 13140B-P



Quick Specs

Material
Certifications



Nylon 6/6
Certified by UL for Compliance with both Canadian and U.S. requirements under File E54523

Flammability Rating
Temperature Range

94V-2
-40°F (-40°C) to 185°F (85°C)