

## Power PCB Relay T9E

- 1 pole 30A, 1 formA(NO) or 1 formC(CO)
- High breaking capacity 7500 VA
- PCB and PCB/quick connect terminals
- UL class F insulation as standard
- Ambient temperature up to 105°C
- Plastic materials according to IEC60335-1

### Typical applications

HVAC, power supplies, domestic appliances, measurement and control.



### Approvals

VDE 40027903, UL E58304

Technical data of approved types on request.

### Contact Data

Contact arrangement	1 form A (NO)	1 form C (CO)
Rated voltage	240VAC	
Max. switching voltage	250VAC (VDE); 300VAC (UL)	
Rated current	30A	20A/10A
Limiting continuous current	30A	
Breaking capacity max.	7500VA	5000/2500VA
Contact material	AgSnOInO (AgCdO optional)	
Min. recommended contact load	1A, 5VDC or 12VAC	
Initial contact resistance	75 mΩ at 1A at 5VDC or 12VAC	
Frequency of operation, with/without load	6/120min <sup>-1</sup>	
Operate/release time max., including bounce	15/15ms	

### Contact ratings

Type	Contact	Load	Cycles
------	---------	------	--------

#### IEC 61810

AgSnOInO, 1W coil			
1	NO	30A, 250VAC, cosφ=1, 60°C	20x10 <sup>3</sup>
1	NO	20A, 250VAC, cosφ=1, 85°C	100x10 <sup>3</sup>
2	NO	20A, 250VAC, cosφ=1, 70°C	100x10 <sup>3</sup>
1, 2	CO	20A / 10A, 250VAC, cosφ=1, 60°C	20x10 <sup>3</sup>

AgSnOInO, 900mW coil			
1	NO	17A, 250VAC, cosφ=1, 105°C	100x10 <sup>3</sup>
1	NO	20A, 250VAC, cosφ=1, 85°C	100x10 <sup>3</sup>

#### EN 60730-1

AgSnOInO, 1W coil			
1	NO	12(12)A, 240VAC, 60°C	100x10 <sup>3</sup>

#### UL 508 1)

AgSnOInO, 1W coil			
1, 2	NO	30A, 240VAC, general purpose, 25°C	100x10 <sup>3</sup>
AgSnOInO, 900mW coil			
1, 2	NO	TV-8, 125VAC, 25°C	25x10 <sup>3</sup>

1) Additional UL 508 ratings are available.

Mechanical endurance	10x10 <sup>6</sup> ops.
----------------------	-------------------------

### Coil Data

Coil voltage range	6 to 110VDC
Max. coil power	110% of nominal
Max. coil temperature	155°C
Coil insulation system according UL	Class F

### Coil Data (continued)



#### Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%	Rated coil power W
Code D (1W) coil					
6	6	4.5	0.6	36	1
9	9	6.75	0.9	81	1
12	12	9	1.2	144	1
18	18	13.5	1.8	324	1
22	22	16.5	2.2	484	1
24	24	18	2.4	576	1
48	48	36.2	4.8	2304	1
110	110	82.5	11	12100	1
Code L (900mW) coil					
6	6	4.5	0.6	40	.9
12	12	9	1.2	155	.9
18	18	13.5	1.8	380	.9
24	24	18	2.4	660	.9

All figures are given for coil without preenergization, at ambient temperature +23°C.

### Insulation Data

Initial dielectric strength	
between open contacts	1500V <sub>ms</sub>
between contact and coil	2500V <sub>ms</sub>
Initial surge withstand voltage	
between contact and coil	6kV (1.2μs/50μs impulse wave)
Initial insulation resistance	
between insulated elements	1x10 <sup>9</sup> Ω
Clearance/creepage	
between contact and coil	≥3mm/4mm



Coil operating ranges shown above are for 1W coils.



**Power PCB Relay T9E** (Continued)

**Product code structure**

Typical product code

**T9E S 1 D 1 4 -24**
**Type**
**T9E** Power PCB relay T9E

**Enclosure**
**S** Wash-tight plastic case with knock off nib  
**V** Flux-proof plastic case

**Contact arrangement**
**1** 1 form A (1 NO) **5** 1 form C (1 CO)

**Coil Input**
**D** DC voltage, 1W **L** DC voltage, 900mW

**Mounting and termination**
**1** PCB mounting; PCB terminals for coil and contacts  
**2** PCB mounting; PCB terminals for coil and contacts; 6.35mm (.250in) QC for contacts

**Contact material**
**4** AgSnOInO  
**2** AgCdO – optionally available. Contact Product Engineering for availability and ratings.

**Coil voltage**

Coil code: please refer to coil versions table

Product Code	Enclosure	Mounting	Contact material	Contacts	Coil version	Coil voltage	Part number
T9ES1L14-18	wash tight	PCB terminals	AgSnOInO	1 form A, 1 NO	900mW	18VDC	1-2027234-8
T9ES1D14-12					1W	12VDC	2027234-2
T9ES1D14-24						24VDC	2027234-7
T9ES1D12-12			AgCdO			12VDC	1-2027234-0
T9ES1D24-12		PCB + quick connect	AgSnOInO			12VDC	2027234-8
T9ES1D22-12			AgCdO			12VDC	1-2027243-3
T9ES5D14-12		PCB terminals	AgSnOInO	1 form C, 1 CO		12VDC	2027234-6
T9ES5D12-24			AgCdO			24VDC	2027234-4
T9ES5D24-12		PCB + quick connect	AgSnOInO			12VDC	2027234-9
T9EV1D14-22	flux proof	PCB terminals		1 form A, 1 NO		22VDC	2027234-5