PLC-LOGIC-STARTERKIT3 - Starter kit

2909916

https://www.phoenixcontact.com/us/products/2909916

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

PLC logic starter kit 3, consisting of: plug-in stand-alone logic module (SAM 2), eight relay output terminal blocks with Push-in connection (250 V AC/DC, max. 6 A), and micro USB programming cable

Commercial data

Item number	2909916
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C424
Product key	CK26Z2
Catalog page	Page 434 (C-5-2019)
GTIN	4055626409122
Weight per piece (including packing)	612.7 g
Weight per piece (excluding packing)	600 g
Customs tariff number	85371098
Country of origin	DE

PLC-LOGIC-STARTERKIT3 - Starter kit

2909916

https://www.phoenixcontact.com/us/products/2909916

Set consists of

PLC-V8C/PT-24DC/SAM2 - Controller

2907443

https://www.phoenixcontact.com/us/products/2907443

PLC logic stand-alone module, Generation 2, with 16 I/Os, for plug-in connection to eight digital or analog PLC-INTERFACE terminal blocks, cannot be extended, real-time clock, micro USB female connector, accommodates memory module and Bluetooth adapter, Push-in connection

PLC-RPT- 24DC/ 1/ACT - Relay Module

2900312

https://www.phoenixcontact.com/us/products/2900312

PLC-INTERFACE for output functions, consisting of PLC-BPT.../ACT basic terminal block with push-in connection and plug-in miniature relay with power contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 24 V DC

PLC-LOGIC-STARTERKIT3 - Starter kit

2909916

https://www.phoenixcontact.com/us/products/2909916

CAB-USB A/MICRO USB B/2,0M - Connecting cable

2701626

https://www.phoenixcontact.com/us/products/2701626

Connecting cable, for connecting the controller to a PC for PC Worx and LOGIC+, USB A to micro USB B, 2 m in length.

Technical data

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed.

Product properties

Product type	Starter kit

Mounting

Mounting type	DIN rail mounting

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2909916

	EAC
	Approval ID: RU C-DE.A*30.B.01082

Classifications

ECLASS

ECLASS-11.0	27242219
ECLASS-12.0	27242219
ECLASS-13.0	27242219

ETIM

ETIM 8.0	EC002581

UNSPSC

UNSPSC 21.0	32151700

Environmental product compliance

REACh SVHC	Lead 7439-92-1
	Hexahydromethylphthalic anhydride

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"