

## Sensor/Actuator cable - SAC-5P-MR/5,0-647 SCO BK - 1410215

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/Actuator cable, 5-position, TPE, yellow RAL 1021, Plug angled M12 SPEEDCON, A-coded, on free cable end, Cable length: 5 m



### Key Commercial Data

|                                      |               |
|--------------------------------------|---------------|
| Packing unit                         | 1 pc          |
| Weight per Piece (excluding packing) | 800.0 g       |
| Country of origin                    | United States |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 5 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
| Degree of protection            | IP65/IP67                        |

#### General

|                              |                               |
|------------------------------|-------------------------------|
| Rated current at 40°C        | 4 A                           |
| Rated voltage                | 60 V                          |
| Number of positions          | 5                             |
| Coding                       | A - standard                  |
| Standards/regulations        | M12 connector IEC 61076-2-101 |
| Status display               | No                            |
| Protective circuit/component | Unwired                       |
| Overvoltage category         | II                            |
| Degree of pollution          | 3                             |
| Torque                       | 0.4 Nm (M12 connector)        |

## Sensor/Actuator cable - SAC-5P-MR/5,0-647 SCO BK - 1410215

### Technical data

#### Material

|  |   |
|--|---|
| Flammability rating according to UL 94 | HB  |
| Contact material                       | CuSn  |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Material, knurls                       | Zinc die-cast, nickel-plated                |

#### Standards and Regulations

|  |                 |
|--|-----------------|
| Standard designation                   | M12 connector   |
| Standards/regulations                  | IEC 61076-2-101 |
| Flammability rating according to UL 94 | HB              |

#### Cable

|                                    |   |
|------------------------------------|---|
| Cable type                         | TPE yellow 105 °C                             |
| Cable type (abbreviation)          | 647   |
| UL AWM style                       | 20327 (105°C/300 V)                           |
| AWG signal line                    | 18  |
| Conductor structure signal line    | 41x 0.16 mm                                   |
| Core diameter including insulation | 1.8 mm  |
| Thickness, insulation              | 0.23 mm                                       |
| Overall twist                      | 5 wires around filler to the core             |
| External sheath, color             | yellow  |
| Outer sheath thickness             | 0.89 mm                                       |
| External cable diameter D          | 6.6 mm ±0.25 mm                               |
| Cable weight                       | 39 kg/km                                      |
| Outer sheath, material             | TPE   |
| Material conductor insulation      | PVC   |
| Nominal voltage, cable             | 300 V   |
| Flame resistance                   | According to FT1                              |
| Resistance to oil                  | OIL RES I according to UL 2256                |
| Other resistance                   | UV resistant (720 h) to UL 2256               |
| Ambient temperature (operation)    | -30 °C ... 105 °C (cable, fixed installation) |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27061804 |
| eCl@ss 6.0 | 27061801 |

# Sensor/Actuator cable - SAC-5P-MR/5,0-647 SCO BK - 1410215

## Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |

## Accessories

### Accessories

#### Protective cap

Sealing cap - PROT-M12 FS-PA-CHAIN - 1430873

M12 sealing cap made of plastic with fixing band, for sensor cables, for free M12 sockets



#### Safety locking

Locking clip - SAC-M12-EXCLIP-M - 1558988



Locking clip for the pin side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools

#### Screwdriver tools

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

Tool - SAC BIT M12-D15 - 1208432



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

# Sensor/Actuator cable - SAC-5P-MR/5,0-647 SCO BK - 1410215

## Accessories

---

### Torque tool

Torque screwdriver - TSD 04 SAC - 1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

---

Torque screwdriver - TSD-M 1,2NM - 1212224




Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

---


## Drawings

Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side


Cable cross section




TPE yellow 105 °C [647]

## Sensor/Actuator cable - SAC-5P-MR/5,0-647 SCO BK - 1410215

Dimensional drawing



Circuit diagram



Contact assignment of the M12 plug

M12 x 1 male plug, angled