Handwheels for position indicators

INCH



































MATERIAL

Glass-fibre reinforced polyamide based (PA) technopolymer, black colour, matte finish.

Technopolymer

STANDARD EXECUTIONS

Black-oxide steel boss, standard reamed hole (on page -), fitting to shaft by means of a supplied grub screw with hexagon socket and cup end UNI 5929-85.

- VHT-GXX: for gravity indicators.
- VHT-PXX: for positive drive indicators.

Rear flange with internal crown gear wheel in acetal resin based (POM) technopolymer. Black-oxide steel screw and anchor pin.

FEATURES AND APPLICATIONS

The lobed shape with no cavities prevents unhealthy residues from depositing. Particularly suitable for applications on machines and equipment whose parts must be frequently cleaned by using water jets

INDICATOR CHOICE (TO BE ORDERED SEPARATELY)

To choose the indicator see the table below for possible assembly with indicators.


See also "Assembly instructions" for gravity indicators type G (on page 724) or positive drive indicators type P (on page 726).


ACCESSORIES ON REQUEST

- Cover CP-XX (see page 753) for use without the indicator.



ELESA Original design





VHT-GXX

	INCH	
_		_

Code	Description	D	L	d	h	d1	d2	d3	f	h1	l1	13	47	Handwheel indicator combinations
CE930255	VHT.85-GXX1 A-5/16	3.35	2.01	0.312	0.67	0.94	0.71	2.28	M5	0.24	0.61	0.71	0.24	GA01 - GA11
CE930351	VHT.110-GXX2 A-3/8	4.33	2.28	0.375	0.87	1.1	0.87	3.03	M5	0.24	0.79	0.71	0.4	GA02 - GA12 - GW12
CE930355	VHT.110-GXX2 A-1/2	4.33	2.28	0.500	0.87	1.1	0.87	3.03	M5	0.24	0.79	0.71	0.39	GA02 - GA12 - GW12

VHT-PXX

INCH

Code	Description	D	L	d	h	d1	d3	d5	f	f1	h1	l1	12	13	I 4	R	Δ'Δ	Handwheel indicator combinations
CE930252	VHT.85-PXX1 A-5/16	3.35	2.17	0.312	0.81	0.71	2.28	0.24	M5	M4	0.2	0.73	0.41	0.71	0.57	0.75	0.29	PA01 - PA11
CE930352	VHT.110-PXX2 A-3/8	4.33	2.28	0.375	0.87	1.18	3.03	0.24	M5	M4	0.24	0.79	0.47	0.71	0.52	1.12	0.64	PA02 - PA12 - PW12



738