

# Endoscope with Telescoping Pole PCE-IVE 330



**Industrial endoscope PCE-IVE 330 for diagnosis and monitoring of hard-to-reach areas/  
machine and system diagnostics / 8" LCD monitor / 12 bright LEDs on the camera head/  
adjustable brightness of the LEDs / memory function / video function /flexible camera head**

The industrial endoscope is used to diagnose and monitor hard-to-reach areas on machines and systems. Due to the length of the industrial endoscope, it is also possible to detect areas which are difficult to access. Visual monitoring with the telescopic camera is supported by the flexible camera head. It can be brought into the desired position by bending, and thus images at a certain angle are also made possible. On the camera are 12 bright LEDs, which illuminate the area in which the telescopic camera is to be used, very well, so that a clear picture can be transferred to the display. The brightness of the LEDs can be adjusted using a dial on the handle of the telescopic camera.

Thus, the telescopic camera can also detect potential hazards inside the machine. For example, fracture points on components are made clear by this telescopic camera. In addition to the normal mode in which the images only are transmitted to the display, a video recording can also be performed if an SD card is inserted. Thus, the performance characteristics of individual components can also be monitored and, if necessary, optimized later.

The scope of delivery of the telescopic camera includes not only the SD card, but also a card reader so that the produced video can later be easily viewed on the PC. In order for the videos to be correctly ordered when they are started on the computer, the telescope camera automatically adds the date and time to the video. Thus, no confusion can occur. However, the date and time must first have been set correctly on the device.

- ▶ flexible camera head
- ▶ 8" LCD monitor
- ▶ brightness-adjustable LEDs
- ▶ up to three meters long
- ▶ video function
- ▶ SD card slot as storage option

## Specifications

### Camera

Camera head	1/4 CMOS
Pixel	0.3 megapixel
Lighting	12 x LED (white)
Camera length	320 mm
Camera diameter	23 mm
LCD monitor	8"
Resolution	800 * 480
Dimensions	130 x 80 x 10 mm
Telescopic rod	
Maximum length	2.3 m
Minimal length	0.9 m
Battery	
Battery capacity	1500 mAh
Output voltage	12 V DC, 500 mA
Charging adapter	
Input voltage	100 ... 240 V AC, 50 / 60 Hz
Output voltage	12 V DC, 500 mA
DVR	
PAL output	704 x 576 (PAL)
Video format	MPEG-4
Recording format	ASF
SD card	2 ... 32 GB
General information	
Length	maximum length: 3 m
Operating voltage	12 V DC
Environmental conditions	-20 ... +50 °C

## More information

Manual



More product info



Similar products



Subject to change