


# CBT-90 LEDs



## Table of Contents

- Technology Overview .....2
- Test Specifications .....2
- White Binning Structure ....3
- White Chromaticity Bins ....4
- Green, Blue Binning Structure .....5
- Product Shipping & Labeling Information.....6
- White Electrical Characteristics .....7
- White Optical and Electrical Characteristics .....8
- Green/Blue Optical and Electrical Characteristics.....9
- Green/Blue Lifetime and Lumen Maintenance..... 13
- Radiation Patterns ..... 14
- Thermal Resistance ..... 15
- Mechanical Dimensions .. 16
- Ordering Information .... 17

## Features:

- Extremely high optical output:
  - Over 2,250 White Lumens
  - Over 1,800 Green lumens
  - Over 650 Blue Lumens
- High thermal conductivity package - junction to case thermal resistance of only 0.8°C/W
- CBT-90-W available in 5700K and 6500K Color points (typ)
- Large, monolithic chip with uniform emitting area of 9 mm<sup>2</sup>
- Unencapsulated die with low profile protective window optimizes optical coupling in etendue-limited applications
- Lumen maintenance of greater than 70% after 60,000 hours
- Environmentally friendly: RoHS and Halogen compliant

## Applications

- Fiber-coupled Illumination
- Architectural and Entertainment Lighting
- Medical Lighting
- Machine Vision
- Microscopy
- Displays and Signage
- General Illumination
- Spot Lighting
- Emergency Vehicle Lighting
- Projection Systems

## Technology Overview

Luminus LEDs™ benefit from a suite of innovations in the fields of chip technology, packaging and thermal management. These breakthroughs allow illumination engineers and designers to achieve solutions that are high brightness and high efficiency.

### LED Technology

Luminus LED™ technology enables large area LED chips with uniform brightness over the entire LED chip surface. The optical power and brightness produced by these large monolithic chips enable solutions which replace arc and halogen lamps where arrays of traditional high power LEDs cannot.

### Packaging Technology

Thermal management is critical in high power LED applications. With a thermal resistance from junction to case of 0.8° C/W, Luminus CBT-90 LEDs have the lowest thermal resistance of any LED on the market. This allows the LED to be driven at higher current densities while maintaining a low junction temperature, thereby resulting in brighter solutions and longer lifetimes.

### Reliability

Luminus LEDs are one of the most reliable light sources in the world today. LEDs have passed a rigorous suite of environmental and mechanical stress tests, including mechanical shock, vibration, temperature cycling and humidity, and have been fully qualified for use in extreme high power and high current applications. With very low failure rates and median lifetimes that typically exceed 60,000 hours, Luminus LEDs are ready for even the most demanding applications. (Refer to Luminus' Reliability application note for more information.)

### Environmental Benefits

Luminus LEDs help reduce power consumption and the amount of hazardous waste entering the environment. All LED products manufactured by Luminus are RoHS and REACH compliant and free of hazardous materials, including lead and mercury.

## Luminus LED Test Specifications

Every Luminus LED is fully tested to ensure that it meets the high quality standards expected from Luminus' products.

### Testing Temperature

Luminus core board products are measured in an equivalent way the devices will operate in a system. The device is mounted on a 40°C heat sink and allowed to reach thermal equilibrium under full power. The measurement is taken after equilibrium is reached. This method of measurement ensures that Luminus LEDs perform in the field just as they are specified.

### Specification Measurement Condition (9A, 13.5 A)

The tables on the following pages provide typical optical and electrical characteristics measured at 9A for white, 13.5A for Green and Blue. The associated junction temperature is  $T_j = 70$  °C for white and  $T_j = 75$  ° - 90 ° C for GB. The CBT-90 can be operated over a wide range of current drive conditions from 200mA to 18A and duty cycle from <1% to 100%).

### CBT-90 White Binning Structure

CBT-90 white LEDs are tested for luminous flux and chromaticity at a drive current of 9.0 A (1.0 A/mm<sup>2</sup>) and placed into one of the following luminous flux (FF) and chromaticity (WW) bins:

#### Flux Bins ( At Test Condition \*)


| Color  | Flux Bin (FF) | Minimum Flux (lm) at 9.0A | Maximum Flux (lm) at 9.0A |
|--|---------------|---------------------------|---------------------------|
| W57S (5700K) and W65S (6500K)<br>6500K, Standard CRI (typ. 70) | MA            | 1,380                     | 1,485                     |
|  | MB            | 1,485                     | 1,590                     |
|  | NA            | 1,590                     | 1,710                     |
|  | NB            | 1,710                     | 1,830                     |
|  | PA            | 1,830                     | 1,966                     |
|  | PB            | 1,966                     | 2,100                     |
| W57H<br>5700K, High CRI (typ. 92)<br>(Pending End of Life)     | KA            | 1,080                     | 1,120                     |
|  | KB            | 1,120                     | 1,200                     |
|  | LA            | 1,200                     | 1,290                     |
|  | LB            | 1,290                     | 1,380                     |

\*Note: Luminus maintains a +/- 6% tolerance on flux measurements.

Luminus maintains a +/- 2% tolerance on CRI measurements.

#### Chromaticity Bins

Luminus' Standard Chromaticity Bins: 1931 CIE Curve



**CBT-90 White Chromaticity Bins**

The following tables describe the four chromaticity points that bound each chromaticity bin. Chromaticity bins are grouped together based on the color temperature.

| 6500K Chromaticity Bins |       |       |
|-------------------------|-------|-------|
| Bin Code (WW)           | CIEx  | CIEy  |
| DG                      | 0.307 | 0.311 |
|                         | 0.322 | 0.326 |
|                         | 0.323 | 0.316 |
|                         | 0.309 | 0.302 |
| F3*                     | 0.305 | 0.321 |
|                         | 0.313 | 0.329 |
|                         | 0.315 | 0.319 |
|                         | 0.307 | 0.311 |
| F4*                     | 0.303 | 0.330 |
|                         | 0.312 | 0.339 |
|                         | 0.313 | 0.329 |
|                         | 0.305 | 0.321 |
| G3*                     | 0.313 | 0.329 |
|                         | 0.321 | 0.337 |
|                         | 0.322 | 0.326 |
|                         | 0.315 | 0.319 |
| G4*                     | 0.312 | 0.339 |
|                         | 0.321 | 0.348 |
|                         | 0.321 | 0.337 |
|                         | 0.313 | 0.329 |
| EF                      | 0.302 | 0.335 |
|                         | 0.320 | 0.354 |
|                         | 0.321 | 0.348 |
|                         | 0.303 | 0.330 |
| DE                      | 0.283 | 0.304 |
|                         | 0.303 | 0.330 |
|                         | 0.307 | 0.311 |
|                         | 0.289 | 0.293 |
| DF                      | 0.289 | 0.293 |
|                         | 0.307 | 0.311 |
|                         | 0.309 | 0.302 |
|                         | 0.293 | 0.285 |

| 5700K Chromaticity Bins |       |       |
|-------------------------|-------|-------|
| Bin Code (WW)           | CIEx  | CIEy  |
| DJ                      | 0.322 | 0.324 |
|                         | 0.337 | 0.337 |
|                         | 0.336 | 0.326 |
|                         | 0.323 | 0.314 |
| H3*                     | 0.321 | 0.335 |
|                         | 0.329 | 0.342 |
|                         | 0.329 | 0.331 |
|                         | 0.322 | 0.324 |
| H4*                     | 0.321 | 0.346 |
|                         | 0.329 | 0.354 |
|                         | 0.329 | 0.342 |
|                         | 0.321 | 0.335 |
| J3*                     | 0.329 | 0.342 |
|                         | 0.337 | 0.349 |
|                         | 0.337 | 0.337 |
|                         | 0.330 | 0.331 |
| J4*                     | 0.329 | 0.354 |
|                         | 0.338 | 0.362 |
|                         | 0.337 | 0.349 |
|                         | 0.329 | 0.342 |
| EH                      | 0.320 | 0.352 |
|                         | 0.338 | 0.368 |
|                         | 0.338 | 0.362 |
|                         | 0.321 | 0.346 |

\*Sub-bins within ANSI defined quadrangles per ANSI C78.377-2008

**CBT-90 Green/Blue Bin Structure**

*CBT-90 G/B: Not recommended for new designs. Please consider CBT-90 TE version instead as documented in PDS-002547 datasheet*

All CBT-90 monochromatic LEDs are tested for luminous flux/ dominant wavelength and placed into one of the following flux/ wave length bins. The binning structure is universally applied across each monochromatic color of the CBT-90 product line. Consult the local sales person for the available flux/ wavelength bins for the product:

**Flux Bins (At Test Condition\*)**

| Color | Luminous Flux Bin (FF) | Minumum Flux (lm) @ 13.5A | Maximum Flux (lm) @ 13.5A |
|-------|------------------------|---------------------------|---------------------------|
| Green | CK                     | 1,500                     | 2,000                     |
|       | CM                     | 2,000                     | 2,300                     |
| Blue  | DJ                     | 250                       | 350                       |
|       | DK                     | 350                       | 450                       |
|       | DM                     | 450                       | 575                       |

**Dominant Wavelength Bins**

| Color | Wavelength Bin (FF) | Minumum Wavelength @ 13.5A | Maximum Wavelength @ 13.5A |
|-------|---------------------|----------------------------|----------------------------|
| Green | G4                  | 520                        | 525                        |
|       | G5                  | 525                        | 530                        |
|       | G6                  | 530                        | 535                        |
|       | G7                  | 535                        | 540                        |
| Blue  | B4                  | 450                        | 455                        |
|       | B5                  | 455                        | 460                        |
|       | B6                  | 460                        | 465                        |
|       | B7                  | 465                        | 470                        |

\*Note: Luminus maintains a +/- 6% tolerance on flux measurements.

## Product Shipping & Labeling Information

All CBT-90 products are packaged and labeled with their respective bin as outlined in the tables and charts on pages 3, 4, & 5. When shipped, each package will only contain one bin. The part number designation is as follows:

### CBT-90 White

**CBT** — **90** — **WNNX** — **C11** — **FF** — **WW**

| Product Family              | Chip Area               | Color                         | Package Configuration | Flux Bin            | Chromaticity Bin    |
|-----------------------------|-------------------------|-------------------------------|-----------------------|---------------------|---------------------|
| CBT: Chip on Board (window) | 90: 9.0 mm <sup>2</sup> | CCT & CRI<br>See Note 1 below | Internal Code         | See page 3 for bins | See page 4 for bins |

Note 1: *WNNX nomenclature corresponds to the following:*

*W = White*

*NN = color temperature, where:*

*57 corresponds to 5700K*

*65 corresponds to 6500K*

*X = color rendering index, where:*

*S (standard) corresponds to a typical CRI of 70*

*H (High) corresponds to a typical CRI of 92*

#### Example 1:

The part label CBT-90-W65S-C11-NA-G4 refers to a 6500K standard CRI white, CBT-90 emitter, with a flux range from 1,590 to 1,710 lumens and a

### CBT-90 Green/Blue<sup>2</sup>

*CBT-90 G/B: Not recommended for new designs. Please consider CBT-90 TE version instead as documented in PDS-002547 datasheet*

**CBT** — **90** — **X** — **C11** — **FF** — **WW**

| Product Family              | Chip Area               | Color               | Package Configuration | Flux Bin            | Wavelength Bin      |
|-----------------------------|-------------------------|---------------------|-----------------------|---------------------|---------------------|
| CBT: Chip on Board (window) | 90: 9.0 mm <sup>2</sup> | G: Green<br>B: Blue | Internal Code         | See page 5 for bins | See page 5 for bins |

Note 2: *X nomenclature corresponds to the following:*

*G = Green*

*B = Blue*

#### Example 2:

The part number CBT-90-B-C11-DK-B6 refers to a blue, CBT-90 module, with a flux range 350-400 lumens and a wavelength range 460 nm to 465 nm.

**CBT-90 White Electrical Characteristics<sup>1</sup>**
**Optical and Electrical Characteristics**

| Drive Condition <sup>2</sup> |                    | 9.0 A Continuous        |                   |
|------------------------------|--------------------|-------------------------|-------------------|
| Parameter                    | Symbol             | Values at Test Currents | Unit              |
| Current Density              | j                  | 1.0                     | A/mm <sup>2</sup> |
| Forward Voltage              | V <sub>F,min</sub> | 2.9                     | V                 |
|                              | V <sub>F,typ</sub> | 3.3                     | V                 |
|                              | V <sub>F,max</sub> | 3.8                     | V                 |

**Common Characteristics**

| Parameter  | Symbol         | Values      | Unit            |
|--|----------------|-------------|-----------------|
| Emitting Area  |                | 9.0         | mm <sup>2</sup> |
| Emitting Area Dimensions                             |                | 3 x 3       | mm×mm           |
| Color Temperature <sup>3</sup> (typ)                 | CCT            | 5,700/6,500 | K               |
| Color Rendering Index <sup>4</sup> (Typical)         | R <sub>a</sub> | 72          |                 |
| Forward Voltage Temperature Coefficient <sup>5</sup> |                | -5.47       | mV/°C           |

**Absolute Maximum Ratings**

| Parameter                                 | Symbol             | Values   | Unit |
|---|--------------------|----------|------|
| Absolute Minimum Operating Current        |                    | 0.2      | A    |
| Maximum Current <sup>6</sup>              |                    | 18       | A    |
| Maximum Junction Temperature <sup>7</sup> | T <sub>j-max</sub> | 150      | °C   |
| Storage Temperature Range                 |                    | -40/+100 | °C   |

Note 1: All measured values are with a constant heat sink temperature  $T_{heat\ sinks} = 40^{\circ}C$ .

Note 2: CBT-90 white devices can be driven at currents ranging from 1A to 18A and at duty cycles ranging from 1% to 100%. Drive current and duty cycle should be adjusted as necessary to maintain the junction temperature desired to meet application lifetime requirements. In pulsed operation, rise time from 10-90% of forward current should be larger than 0.5 microseconds

Note 3: CCT value based off of CIE measurement. CIE measurement uncertainty for white devices is estimated to be +/- 0.01.







Note 4: Color Rendering Index (CRI) is measured to within + or - 2.

Note 5: Forward voltage temperature coefficient at current density of 1.0 A/mm<sup>2</sup>. Contact Luminus for value at other drive conditions.

Note 6: CBT-90 White LEDs are designed for operation to an absolute maximum forward drive current density of 2.0 A/mm<sup>2</sup>. Product lifetime data is specified at recommended forward drive currents.

Note 7: Lifetime dependent on LED junction temperature. Input power and thermal system must be properly managed to ensure lifetime. See charts on pg 8 for further information.

Note 8: Special design considerations must be observed for operation under 1 A. Please contact Luminus for further information.

**CBT-90 White Optical & Electrical Characteristics**
**Relative Output Flux vs. Forward Current**

**Mean Lifetime<sup>1</sup>**

**Typical Spectrum<sup>3</sup>**

**Forward Current vs. Forward Voltage**

**Lumen Maintenance vs. Time<sup>2</sup>**

**Current Derating Curve**


Note 1: Mean expected lifetime in dependence of junction temperature at 1.0 A/mm<sup>2</sup> in continuous operation. Lifetime defined as time to 70% of initial intensity. Based on lifetime test data. Data can be used to model failure rate over typical product lifetime (contact Luminus for lifetime reliability test data for 1A/mm<sup>2</sup> condition).



Note 2: Lumen maintenance in dependence of time at 1.0 A/mm<sup>2</sup> in continuous operation with junction temperatures of 130 °C.

Note 3: Typical spectrum at current density of 1.0 A/mm<sup>2</sup> in continuous operation.





**CBT-90 Green/Blue Optical & Electrical Characteristics**
*CBT-90 G/B: Not recommended for new designs. Please consider CBT-90 TE version instead as documented in PDS-002547 datasheet*

| Green                                    |                    |                      |                   |
|--|--------------------|----------------------|-------------------|
| Drive Condition <sup>(1,2)</sup>         |                    | 13.5 A<br>Continuous |                   |
| Parameter                                | Symbol             | Values <sup>4</sup>  | Unit              |
| Current Density                          | J                  | 1.5                  | A/mm <sup>2</sup> |
| Forward Voltage                          | V <sub>F</sub> min | 3.2                  | V                 |
|  | V <sub>f</sub>     | 4.2                  | V                 |
|  | V <sub>F</sub> max | 5.2                  | V                 |
| Luminous Flux <sup>3</sup>               | Φ <sub>v</sub>     | 2,150                | lm                |
| Radiometric Flux                         | Φ <sub>r</sub>     | 4.2                  | W                 |
| Luminous Efficacy                        | η                  | 38                   | lm/W              |
| Dominant Wavelength <sup>4</sup>         | λ <sub>d</sub>     | 530                  | nm                |
| Peak Wavelength                          | λ <sub>p</sub>     | 523                  | nm                |
| FWHM                                     | Δλ <sub>1/2</sub>  | 36                   | nm                |
| Chromaticity<br>Coordinates <sup>5</sup> | x                  | 0.192                | -                 |
|  | y                  | 0.700                | -                 |

**Relative Output Flux vs. Forward Current<sup>1</sup>**

**Forward Current vs. Forward Voltage**

*Notes: See page 12*

**CBT-90 Green/Blue Optical & Electrical Characteristics**

| Blue                                  |                       |                     |                   |
|---------------------------------------|-----------------------|---------------------|-------------------|
| Drive Condition <sup>(1,2)</sup>      |                       | 13.5 A Continuous   |                   |
| Parameter                             | Symbol                | Values <sup>4</sup> | Unit              |
| Current Density                       | J                     | 1.5                 | A/mm <sup>2</sup> |
| Forward Voltage                       | $V_{F\ min}$          | 2.8                 | V                 |
|                                       | $V_f$                 | 3.4                 | V                 |
|                                       | $V_{F\ max}$          | 4.0                 | V                 |
| Luminous Flux <sup>3</sup>            | $\Phi_{V\ typ}$       | 425                 | lm                |
| Radiometric Flux                      | $\Phi_r$              | 9.5                 | W                 |
| Luminous Efficacy                     | $\eta$                | 10                  | lm/W              |
| Dominant Wavelength <sup>4</sup>      | $\lambda_d$           | 460                 | nm                |
| Peak Wavelength                       | $\lambda_p$           | 455                 | nm                |
| FWHM                                  | $\Delta\lambda_{1/2}$ | 20                  | nm                |
| Chromaticity Coordinates <sup>5</sup> | x                     | 0.144               | -                 |
|                                       | y                     | 0.038               | -                 |

**Relative Output Flux vs. Forward Current<sup>1</sup>**

**Forward Current vs. Forward Voltage**


Notes: See page 12

**CBT-90 Green/Blue Reference Optical & Electrical Characteristics**
**Common Characteristics**

|  | Symbol | Green   | Blue    | Unit            |
|--|--------|---------|---------|-----------------|
| Emitting Area  |        | 9.0     | 9.0     | mm <sup>2</sup> |
| Emitting Area Dimensions                             |        | 3.0x3.0 | 3.0x3.0 | mmxmm           |
| Thermal Coefficient of Photometric Flux              |        | -0.18   | -0.007  | %/ °C           |
| Thermal Coefficient of Radiometric Flux              |        | -0.20   | -0.17   | %/ °C           |
| Thermal Coefficient of Junction Voltage <sup>6</sup> |        | -4.6    | -3.5    | mV/ °C          |

|   | Symbol            | Green    | Blue     | Unit |
|---|-------------------|----------|----------|------|
| Absolute Minimum Operating Current          |                   | 0.2      | 0.2      | A    |
| Maximum Current                             |                   | 18       | 18       | A    |
| Maximum Junction Temperature <sup>7,8</sup> | T <sub>jmax</sub> | 150      | 150      | °C   |
| Storage Temperature Range                   |                   | -40/+100 | -40/+100 | °C   |

Note 1: All ratings are based on operation with a constant  $T_{heat\ sink} = 40^{\circ}C$ .

Note 2: CBT-90 RGB devices can be driven at currents ranging from 200mA to 18 A and at duty cycles ranging from 1% to 100%. Drive current and duty cycle should be adjusted as necessary to maintain the junction temperature desired to meet application lifetime requirements.

Note 3: Total flux from emitting area at listed dominant wavelength.

Note 4: Minimum and Maximum Dominant Wavelengths are based on typical values +/- 5nm for Red, +/- 8nm for Green and +/- 6nm for Blue.

Note 5: For reference only.






Note 6: Forward voltage temperature coefficient at current density of 1.0 A/mm<sup>2</sup>. Contact Luminus for value at other drive conditions.

Note 7: CBT-90 G,B LEDs are designed for operation to an absolute maximum current as specified above. Product lifetime data is specified at recommended forward drive currents. Sustained operation at or beyond absolute maximum currents will result in a reduction of device lifetime compared to recommended forward drive currents. Actual device lifetimes will also depend on junction temperature. Refer to the lifetime derating curves for further information. In pulsed operation, rise time from 10-90% of forward current should be larger than 0.5 microseconds.

Note 8: Lifetime dependent on LED junction temperature. Input power and thermal system must be properly managed to ensure lifetime. See charts on pg 13 for further information.

Note 9: Special design considerations must be observed for operation under 1 A. Please contact Luminus for further information.

Note 10: Caution must be taken not to stare at the light emitted from these LEDs. Under special circumstances, the high intensity could damage the eye.

**CBT-90 Green/Blue Lifetime and Lumen Maintenance**
**Light Output and Spectral Characteristics Over Heat Sink Temperature**

**Median Lifetime Estimate vs. T<sub>j</sub><sup>1</sup>**

**Lumen Maintenance<sup>2</sup>**

**Typical Spectrum<sup>3</sup>**



Note 1: Median lifetime estimate as a function of junction temperature at 0.35A/mm<sup>2</sup> in continuous operation. Lifetime defined as time to 70% of initial intensity. Based on preliminary lifetime test data. Data can be used to model failure rate over typical product lifetime.

Note 2: Lumen maintenance vs. time at 0.35A/mm<sup>2</sup> in continuous operation, Red junction temperature of 70°C, Green junction temperatures of 120°C, Blue junction temperatures of 100°C.


Note 3: Typical spectrum at current density of 0.35 A/mm<sup>2</sup> in continuous operation.

## Typical Radiation Patterns


Typical Polar Radiation Pattern for White, Green and Blue



Typical Angular Radiation Pattern for White, Green and Blue



## Thermal Resistance



### Typical Thermal Resistance

|                         |           |
|-------------------------|-----------|
| $R_{\theta j-b}^{-1}$   | 0.80 °C/W |
| $R_{\theta b-hs}^{-1}$  | 0.12 °C/W |
| $R_{\theta j-hs}^{-2}$  | 0.92 °C/W |
| $R_{\theta j-ref}^{-1}$ | 0.83 °C/W |


Note 1: Thermal resistance values are based on FEA model results correlated to measured  $R_{\theta j-hs}$  data.


Note 2: Thermal resistance is measured using eGraf 1205 thermal interface material.


## Thermistor Information

The thermistor used in CBT-90 LEDs mounted on core-boards is from Murata Manufacturing Co. The global part number is NCP18XH103J03RB. Please see <http://www.murata.com/> for details on calculating thermistor temperature.

## Electrical Pinout



**Mechanical Dimensions – CBT-90 Emitter**

**GREEN LED DEVICE**

**BLUE LED DEVICE**

**DIMENSIONS IN MILLIMETERS**

| DIMENSION NAME | DESCRIPTION  | NOMINAL DIMENSION | TOLERANCE |
|----------------|--|-------------------|-----------|
| "A"            | TOP OF METAL SUBSTRATE TO TOP OF WINDOW            | .88               | $\pm .13$ |
| "B"            | TOP OF DIE EMITTING AREA TO TOP OF WINDOW          | .65               | $\pm .11$ |
| "C"            | TOP OF METAL SUBSTRATE TO TOP OF DIE EMITTING AREA | .23               | $\pm .02$ |

DWG-002309

Recommended connectors for Anode and Cathode:

- Panduit Disco Lok™ Series P/N: DNF14-250FIB-C
- JST Manufacturing Co: SPS-61T-250

 Thermistor Connector: MOLEX P/N 53780-0270 or GCT P/N WTB08-0215-F.  
 Recommended Female: MOLEX P/N 51146-0200, GCT P/N WTB06-0215-F or equivalent

### Ordering Information

| Ordering Part Number <sup>1,2</sup>    | Color                   | Description  |
|--|-------------------------|--|
| CBT-90-W57S-C11-NA100                  | 5700K White             | White LED™ CBT-90 consisting of a 9 mm <sup>2</sup> LED, thermistor, and connector, mounted on a copper-core PCB   |
| CBT-90-W65S-C11-NA100                  | 6500K White             |  |
| CBT-90-W57H-C11-KB200<br>(Pending EOL) | 5700K White<br>High CRI |  |
| CBT-90-G-C11-JK200                     | Green                   | Green LED™ CBT-90 consisting of 9 mm <sup>2</sup> LED, thermistor, and connector, mounted on a copper-core PCB. <b>CBT-90 G : Product Discontinued. Please consider CBT-90 TE version instead as documented in PDS-002547 datasheet.</b> |
| CBT-90-B-C11-KJ300                     | Blue                    | Blue LED™ CBT-90 consisting of 9 mm <sup>2</sup> LED, thermistor, and connector, mounted on a copper-core PCB. <b>CBT-90 B : Product Discontinued. Please consider CBT-90 TE version instead as documented in PDS-002547 datasheet.</b>  |

Note 1: NA100 - denotes a bin kit comprising of all flux bins with a minimum flux of 1,590 lumens and chromaticity bins at the 6500K color point.

Note 2: KB200 - denotes a bin kit comprising of all flux bins with a minimum flux of 1,120 lumens and chromaticity bins at the 5700K color point.

Note 3: JK200 - denotes a bin kit comprising of all green flux and wavelength bins as specified on page 5

KJ300 - denotes a bin kit comprising of all blue flux and wavelength bins as specified on page 5.

Note 4: For ordering information on all available bin kits, please reference PDS-001694: CBT-90 Binning & Labeling document.

Note 5: Standard packaging increment (SPI) is 10.

Note 6: Red CBT-90 has been discontinued - please refer to PDS-002547 (CBT-90 Thermally Enhanced version) for information on current red product offering

Green- C11 product has been moved to EOL Status - Please consider use of Thermally enhanced version for new design applications.



### History of Changes

| Rev | Date       | Description of Change   |
|-----|------------|---|
| 14  | 09/27/2016 | Clarified applicable minimum operating current  |
|     |            | Editorial Changes   |
|     |            | <i>CBT-90 G/B product discontinued .Please consider CBT-90 TE version instead as documented in PDS-002547 datasheet</i> |
|     |            | Updated thermistor connector information  |
|     |            | Adding 5700K  |

The products, their specifications and other information appearing in this document are subject to change by Luminus Devices without notice. Luminus Devices assumes no liability for errors that may appear in this document, and no liability otherwise arising from the application or use of the product or information contained herein. None of the information provided herein should be considered to be a representation of the fitness or suitability of the product for any particular application or as any other form of warranty. Luminus Devices' product warranties are limited to only such warranties as accompany a purchase contract or purchase order for such products. Nothing herein is to be construed as constituting an additional warranty. No information contained in this publication may be considered as a waiver by Luminus Devices of any intellectual property rights that Luminus Devices may have in such information. LEDs™ is a registered trademark of Luminus Devices, Inc., all rights reserved.

This product is protected by U.S. Patents 6,831,302; 7,074,631; 7,083,993; 7,084,434; 7,098,589; 7,105,861; 7,138,666; 7,166,870; 7,166,871; 7,170,100; 7,196,354; 7,211,831; 7,262,550; 7,274,043; 7,301,271; 7,341,880; 7,344,903; 7,345,416; 7,348,603; 7,388,233; 7,391,059 Patents Pending in the U.S. and other countries.