

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2000

© COPYRIGHT 2000

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	C	ECR-15-007608	30MAY2015	GSK	JB

PN 0-1 As Shown

Contact arrangement
view from connecting side

HVS-HND.17.Bu.C
0-1103279-1
10A 250V 2.5KV 2

STE

31.8

38.1

14.6

Contact arrangement
view from termination side

NOTES

- SUITABLE CRIMP CONTACTS: SERIES HN.D
CUSTOMER DRAWING: 1105050
OUTER DIMENSIONS OF INSULATION: MAX. Ø4mm
- SUITABLE MODULE FIXING FRAME: SERIES HVS SIZE 3 TO 8
CUSTOMER DRAWING: 1103250
- SUITABLE INSERTION TOOL:
CUSTOMER DRAWING: 1102855
- SUITABLE EXTRACTION TOOL:
CUSTOMER DRAWING: 1102855
- STANDARDS:
DIN EN 61984; DIN EN 60664-1

6 POLARIZATION RIPS

7 MARKING OF POLARIZATION ACCORDING TO MARKING OF MODULE FRAME

8 PACKAGING:
10 SETS IN A CARTON, PRE-MOUNTED

PN 0-1 As Shown

HVS-HND.17.Bu.C
0-1103279-1
10A 250V 2.5KV 2

STE

SCALE 1:1

QTY	DESCRIPTION	MATERIAL	COLOR	ITEM NO
1	FEMALE INSERT	PBT-GF10	LIGHT GREY	21
PN 0-1 / HVS-HN.D.17.Bu.C				

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 20.02.2006

SCHNEIDER

CHK 20.02.2006

A.GAST

APVD 20.02.2006

T.SCHNURPFIL

PRODUCT SPEC

108-74083

APPLICATION SPEC

114-74085

WEIGHT

CUSTOMER DRAWING

DIMENSIONS:

mm

MATERIAL

9

TOLERANCES UNLESS

OTHERWISE SPECIFIED:

ISO 8075

DIN 150 2768 mm-E

DIN 16901-120

0 PLC ±

1 PLC ±

2 PLC ±

3 PLC ±

4 PLC ±

ANGLES ±

FINISH

10

NAME

FEMALE INSERT
HVS-HND.17.BU.C

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 00779 C-1103279

SCALE 2:1 SHEET 1 OF 1 REV C

1470-19 (3/11)