



Z34722002-00

LABEL DETAIL
TEXT HIGH 3MM MIN.
TEXT FONT:ARIAL

ENTER DESCRIPTION EC NO: CPG2013-1188 DRWN:FZHANG01 CHKD:BH LONG APPR:XAWANG	QUALITY SYMBOLS FA=0 FC=0 FE=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
			mm	INCH	DRAWN BY	DATE	TITLE		
		4 PLACES	± ---	± ---	FZHANG01	2012/10/26	DVI-D DVI-D DUAL LINK 2M AWG28 EUR		
		3 PLACES	± ---	± ---	CHECKED BY	DATE			
2 PLACES	± ---	± ---	BH LONG	2012/10/26					
1 PLACE	± ---	± ---	APPROVED BY	DATE					
		0 PLACE	± ---	± ---	XAWANG	2012/10/26			
		ANGULAR ± ---°		MATERIAL NO.		DOCUMENT NO.		SHEET NO.	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		687650095		SD-68765-040		1 OF 2	
				SIZE A 4	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

7

6

5

4

3

2

1

- 3. THIS PRODUCT ELECTRICAL PERFORMANCE REFER TO DDWG STANDARD.
- 4. DVI CONNECTOR SPECIFICATION
 - 4.1 REFER TO PRODUCT SPEC. PS74320-001.
 - 4.2 CONTACT PLATING: AU FLASH.
- 5. SHORTCIRCUIT AMONG DRAIN WIRES IS ACCEPTABLE.
- 6. THIS PRODUCT MUST MEET MX RoHS COMPLIANCE.

NOTE:

- 1. OVERMOLD SPECIFICATION
 - 1.1 DVI BOOT MOLDED WITH SNOW WHITE PVC RESIN .
UL94V-0, COLOR: MAD432.
 - HARDNESS (DUROMETER): SHORE A 90-95.
 - 1.2 FERRITE MOLDED WITH BLACK PVC RESIN.
- 2. MECHANICAL SPECIFICATION
 - 2.1 CABLE SHOULD STAND THE PULL FORCE 89-111N FOR 30 SECONDS WITH NO VISIBLE TERMINATION DAMAGE.
 - 2.2 CABLE SHOULD PASS THE FLEX TEST IN 100 CYCLES AT EACH OF PLANES, PER EIA 364-41, CONDITION 1.

SHIELD	SHIELD	GROUND	GROUND
PIN 24	PIN 24	WHITE	TMDS CLOCK-
PIN 23	PIN 23	BROWN	TMDS CLOCK+
PIN 22	PIN 22	BRAID	TMDS CLOCK SHIELD
PIN 21	PIN 21	ORANGE	TMDS DATA 5+
PIN 20	PIN 20	PINK	TMDS DATA 5-
PIN 19	PIN 19	0,5 DRAIN	TMDS DATA 0/5 SHIELD
PIN 18	PIN 18	BLUE	TMDS DATA 0+
PIN 17	PIN 17	WHITE	TMDS DATA 0-
PIN 16	PIN 16	WHITE	HOT PLUG DETECT
PIN 15	PIN 15	ORANGE	GROUND(+5V & HV SYNC)
PIN 14	PIN 14	YELLOW	POWER +5V
PIN 13	PIN 13	BLACK	TMDS DATA 3+
PIN 12	PIN 12	GREY	TMDS DATA 3-
PIN 11	PIN 11	1,3 DRAIN	TMDS DATA 1/3 SHIELD
PIN 10	PIN 10	GREEN	TMDS DATA 1+
PIN 9	PIN 9	WHITE	TMDS DATA 1-
PIN 7	PIN 7	RED	DDC DATA
PIN 6	PIN 6	VIOLET	DDC CLOCK
PIN 5	PIN 5	VIOLET	TMDS DATA 4+
PIN 4	PIN 4	LIGHT BLUE	TMDS DATA 4-
PIN 3	PIN 3	2,4DRAIN	TMDS DATA 2 /4 SHIELD
PIN 2	PIN 2	RED	TMDS DATA 2+
PIN 1	PIN 1	WHITE	TMDS DATA 2-
DVI_D	DVI_D	COLOR	CABLE FUNCTION

ITEM	DESCRIPTION	L(mm)	QTY.
L	LABEL		1
K	FERRITE CORE		2
J	ADHESVE		A/R
I	LOCTITE ACCELERATOR 7455,		A/R
H	COPPER FOIL		2
G	HS F 2mm 105(UL)	5(ref.)	14
F	DVI_D DUAL LINK CABLE 28# CABLE OD:8.6MM	2M REF.	1
E	ACETATE CLOTH	55(ref.)	2
D	PCB		2
C	DVI THUMB SCREW		4
B	ONE BODY CAN		2
A	DVI_D DUAL CHANNEL G/F CONNECTOR		2

ENTER DESCRIPTION EC NO: CPG2013-1188 DRWN:FZHANG01 CHKD:BH LONG APPR:XAWANG	DESCRIPTION 2012/10/26 2012/10/26 2012/10/26	REV B	QUALITY SYMBOLS 	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
						DRAWN BY DATE FZHANG01 2012/10/26		TITLE DVI-D DVI-D DUAL LINK 2M AWG28 EUR		
						CHECKED BY DATE BH LONG 2012/10/26				
						APPROVED BY DATE XAWANG 2012/10/26				
		ANGULAR ±---°		MATERIAL NO. 687650095	DOCUMENT NO. SD-68765-040		SHEET NO. 2 OF 2			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

6

5

4

3

2

1