

Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, glazed door, completely sealed, 500x1250x320mm, IP65, IK08

NSYPLA5123TG

⚠ To be discontinued

⚠ To be discontinued on: 31 August 2023

Main

Range	Thalassa
Product name	Thalassa PLA
Enclosure type	Multi-purpose
Product or component type	Suitable enclosure
Version	PLA
Nominal height	500 mm
Nominal width	1250 mm
Nominal depth	320 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 2 door 2 rear panel

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	2 door(s)
Door opening side	Right and left (120 °)
Lock type	2 points lock, 5 mm double-bar
Accessibility for operation	Front Rear
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	UL 508 A IEC 62208
NEMA degree of protection	NEMA 13 NEMA 2 NEMA 1 NEMA 12
Product certifications	DNV Marine

Electrical insulation class	Class II
-----------------------------	----------

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
-------------------------	--

IK degree of protection	IK08 conforming to IEC 62262 (glazed door)
-------------------------	--

Fire resistance	960 °C conforming to IEC 62208
-----------------	--------------------------------

Ambient air temperature for storage	-35...90 °C
-------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	51.0 cm
------------------	---------

Package 1 Width	128.0 cm
-----------------	----------

Package 1 Length	35.0 cm
------------------	---------

Package 1 Weight	30.681 kg
------------------	-----------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	---

Mercury free	Yes
--------------	-----

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

RoHS exemption information	Yes
----------------------------	-----

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Recommended replacement(s)

NSYPLA5123TG is replaced by:

1x



Floor standing polyester enclosure, Thalassa PLA, plain door, completely sealed, 500x1250x320mm, IP65, IK10

NSYPLA5123G
