


Products

- Products Overview
- Product Search**
- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDF-PVC Heat Shr
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click  to remove) [Search Tips](#)

Part Number > HSTTP75-QY

Your search criteria matched only one product, shown below

HSTTP75-QY



PVC DRY-SHRINK™ Heat Shrink Tubing in Reels

- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance
- Material Type: Polyvinyl Chloride Cross-Linked
- Shrink Ratio: 2:1
- Temperature Range: -4°F to 221°F (-20°C to 105°C)
- Voltage: 600V
- UL VW-1 Recognized, CSA Certified
- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance

Part Number	HSTTP75-QY
RoHS Compliancy Status	Compliant
Note	HSTTP75-QY replaces HSTTP75-Q
Part Description	Flexible, Flame Retardant PVC material offers good cut through and solder resistance.
Material	Polyvinyl Chloride Cross-Linked
Color	Black
CSA Certified	Yes
UL Recognized	E122770
CE Compliant	No
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	25
Length Per Reel (m)	7.6
Max. Recovered I.D. (In.)	0.375
Max. Recovered I.D. (mm)	9.5
Min. Expanded I.D. (In.)	0.750
Min. Expanded I.D. (mm)	19.0
Nominal Diameter (In.)	0.750
Nominal Diameter (mm)	19.0
Nominal Recovered Wall Thickness (In.)	0.035
Nominal Recovered Wall Thickness (mm)	0.9
Pricing Description	Heat Shrink Thin PVC, .75"(19.0mm) Dia Black
Shrink Ratio	2:1
Temperature Range	-4°F – 221°F (-20°C – 105°C)
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.