



har-port RJ45 coupler

Advantages

- Compact and well-shaped service interface in a timeless attractive design
- Easy mounting
- Transmission category 6, performance class E_A, suitable for 1/10 Gigabit Ethernet
- Compact and robust design
- Practical accessories

Technical characteristics

Number of ports	2x RJ45
Transmission performance	Category 6 / class E _A acc. to ISO/IEC 11801:2002, EN 50 173-1
Transmission rate	10/100 Mbit/s and 1/10 Gbit/s
Shielding	Fully shielded, 360° shielding contact
Mounting	Screwable in cover plates
Degree of protection	IP20
Mating cycles	min. 750
Temperature range	-25 °C ... +70 °C
Housing material	Polyamide

Identification	Part number		Drawing	Dimensions in mm	
	silver	black			
har-port RJ45 Cat. 6 coupler	09 45 452 1560	09 45 452 1561			
har-port RJ45 Cat. 6 coupler with cable					
Length: 0.15 m	09 45 452 1500	09 45 452 1530			
0.2 m	09 45 452 1501	09 45 452 1531			
0.3 m	09 45 452 1502	09 45 452 1532			
0.5 m	09 45 452 1504	09 45 452 1534			
0.7 m	09 45 452 1506	09 45 452 1536			
1.0 m	09 45 452 1509	09 45 452 1539			
1.5 m	09 45 452 1510	09 45 452 1540			
2.0 m	09 45 452 1511	09 45 452 1541			
2.5 m	09 45 452 1512	09 45 452 1542			
3.0 m	09 45 452 1513	09 45 452 1543			
3.5 m	09 45 452 1514	09 45 452 1544			
4.0 m	09 45 452 1515	09 45 452 1545			
5.0 m	09 45 452 1516	09 45 452 1546			
7.5 m	09 45 452 1517	09 45 452 1547			
10.0 m	09 45 452 1518	09 45 452 1548			
har-port HIFF coupler housing (for all HIFF compatible modules)	09 45 452 0000	09 45 452 0001			