

Relay connectors - ST-REL7-HG110/4X21 - 2899303

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Relay connector, equipped with Hengstler miniature round relay, contacts (AgCdO+Au): small to large loads, 4 PDT, input voltage 110 V DC, with light indicator, can be plugged on basic termination blocks

The illustration shows version ST-REL 7-HG 24/4X21



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 078829 |
| Weight per Piece (excluding packing) | 104.81 GRM |
| Custom tariff number | 85364900 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 45.6 mm |
| Height | 33 mm |
| Depth | 66.5 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

Coil side

| | |
|---|-----------------|
| Nominal input voltage U_N | 110 V DC |
| Input voltage range in reference to U_N | 0.8 ... 1.1 |
| Typical input current at U_N | 9 mA |
| Typical response time | 15 ms (with DC) |

Relay connectors - ST-REL7-HG110/4X21 - 2899303

Technical data

Coil side

| | |
|---------------------------|---|
| Typical release time | 15 ms (with DC) |
| Operating voltage display | Yes |
| Protective circuit | Damping diode, polarity protection Damping diode, polarity protection diode |

Contact side

| | |
|---------------------------------------|-------------------------|
| Contact type | Single contact, 4-PDT |
| Contact material | AgCdO, hard gold-plated |
| Maximum switching voltage | 250 V AC/DC |
| Maximum inrush current | 6 A |
| Limiting continuous current | 6 A |
| Interrupting rating (ohmic load) max. | 120 W (at 24 V DC) |
| | 180 W (at 48 V DC) |
| | 105 W (at 60 V DC) |
| | 60 W (at 110 V DC) |
| | 90 W (at 220 V DC) |
| | 1250 VA (for 250 V AC) |

General

| | |
|--|----------------------------------|
| Test voltage relay winding/relay contact | 2 kV AC (50 Hz, 1 min.) |
| Test voltage PDT/PDT | 2 kV AC (50 Hz, 1 min.) |
| Operating mode | 100% operating factor |
| Mechanical service life | Approx. 10 ⁷ cycles |
| Standards/regulations | IEC 60664 |
| | IEC 60664 A |
| | DIN VDE 0110 |
| | DIN VDE 0109-11, draft |
| | DIN VDE 0160 (in relevant parts) |
| Pollution degree | 2 |
| Surge voltage category | II |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371104 |
| eCl@ss 4.1 | 27371104 |
| eCl@ss 5.0 | 27371001 |
| eCl@ss 5.1 | 27371001 |

Relay connectors - ST-REL7-HG110/4X21 - 2899303

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 6.0 | 27371001 |
| eCl@ss 7.0 | 27371001 |
| eCl@ss 8.0 | 27371001 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000196 |
| ETIM 3.0 | EC000196 |
| ETIM 4.0 | EC000196 |
| ETIM 5.0 | EC000196 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11 | 39121515 |
| UNSPSC 12.01 | 39121515 |
| UNSPSC 13.2 | 39121515 |

Approvals

Approvals


Approvals

GOST / GOST

Ex Approvals

Approvals submitted

Approval details

| |
|--|
| GOST  |
|--|

Relay connectors - ST-REL7-HG110/4X21 - 2899303

Approvals



Drawings

Circuit diagram

