

Technical Data Sheet

4 Port USB 3.1 Gen 1 Hub with PD Type C Source Port, 12~24V Variable Voltage Input

Model Number: CG-3X2C3AM

Rev 01.200716



The CG-3X2C3AM is a USB3.1 Gen 1 Type-C PD (Power Delivery) Metal Hub that complies with the Universal Serial Bus (USB) Specifications Revision 3.1 Gen 1 and works up to 5Gbps. It provides 1 USB-C PD-Source capable upstream port and 4 downstream facing ports with 1 USB-C and 3 USB-A connectors.

Features

- Compliant with USB3.1 Gen 1 Specification
- Upstream Facing Port: USB-C with PD Source
- Downstream Facing Ports: 1xUSB-C + 3xUSB-A
- Supports 15KV ESD Surge Protection
- PD Supports power source: 20V/5A, 15V/3A, 12V/3A and 5V/3A

Product Information

- Model Number: CG-3X2C3AM
- Packing List:
 - Hub, Power Supply, Screw Lock USB Cable

Specifications

OVERVIEW

Product Type	USB Hub
USB Specification	USB 3.2 Gen 1
Maximum Data Rate	5Gb/sec
Electrical Protections	N/A
Mountable	Surface Mount
Material	Steel
Compliance	N/A

CONNECTIONS

Downstream Port Count	4
Downstream Port Type	1x Type C USB 3.2 G1 / 3.0, 3x Type A USB 3.2 G1 / 3.0
Power Input	12 ~ 24V DC

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
Operating Humidity	5% to 95% RH
Storage Temperature	-20C ~ 75C

DIMENSIONS

Length	7.05 inches
Width	2.33 inches
Height	0.91 inches

OS SUPPORT

Supported Operating Systems	OS independent; No software or drivers required
-----------------------------	---

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

CG-3X2C3AM Product Page	https://www.coolgear.com/product/4-port-usb-3-1-gen-1-hub-with-pd-type-c-source-port-1224v-variable-voltage-input
-------------------------	---

© 2020 Coolgear, Inc. All Rights Reserved. All products and accompanying digital documentation including images are the property and / or trademarks of Coolgear Inc. Coolgear Inc. are continuously improving upon its products. Product specifications are subject to change without notice