Power Double Lock

TE Internal #: 2825340-1

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2

Position, 3.96 mm [.156 in] Centerline, Wire & Cable, UL 94V-0,

Power Double Lock

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire Power Double Lock Plug











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug
Connector System: Wire-to-Wire

Number of Positions: 2

Centerline (Pitch): 3.96 mm [.156 in]

All Glow Wire Power Double Lock Plug (55)

Features

Product Type Features

Stranded
Housing
Plug
Wire-to-Wire
No
Wire & Cable
2
2
2
1



Operating Voltage	50 VAC, 300 VAC
Contact Features	
Contact Current Rating (Max)	14 A
Contact Retention Within Housing	Without
Contact Type	Receptacle
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	PA 66
Usage Conditions	
Operating Temperature Range	-30 - 65 °C[-22 - 149 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)
Packaging Features	
Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233)



Does not contain REACH SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts










Also in the Series | Power Double Lock





Insertion & Extraction Tools(2)









Customers Also Bought









Documents

Product Drawings

PDL 2P PLUG HSG 3.96MM (GWT)

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2825340-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2825340-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2825340-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2 Position, 3.96 mm [. 156 in] Centerline, Wire & Cable, UL 94V-0, Power Double Lock



English