



**SPECIFICATION**  
**MATERIALS:**  
 HOUSING & INSERT: PBT YELLOW  
 COUPLING: BRASS-NICKEL PLATED  
 O-RING: VITON  
**ELECTRICAL:**  
 VOLTAGE: 10-30VDC  
 CURRENT RATING: 4A PER PORT, 12 AMPS MAX.  
 PROTECTION CLASS: IP67  
 OPERATING TEMPERATURE: -5°C to +90°C

**NOTES:**  
 FIXING HOLES TO SUIT M4 SCREWS

DESCRIPTION EC NO.: WEU2010-0450 DRWN: REISSNER 2010/03/19 CHKD: FP APPR: NSTAUDIG 2010/03/23	QUALITY SYMBOLS ▽ = 0 ◻ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE <b>MM ONLY</b>		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
		mm	INCH	DRAWN BY	DATE	<b>MICRO-CHANGE MPIS          8 PORT TOP MOUNT          CABLE PUR</b>		
		4 PLACES ±---	±---	REISSNER	2010/03/19			
		3 PLACES ±---	±---	CHECKED BY	DATE	<b>MOLEX INCORPORATED</b>		
2 PLACES ±---	±---	NS	2010/03/19					
1 PLACE ±0.3	±---	APPROVED BY	DATE	MATERIAL NO.	DOCUMENT NO.	SHEET NO.		
ANGULAR ± --- °		NSTAUDIG	2010/03/23	SEE TABLE	SD-120114-076	1 OF 1		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
1	REV	A3						