

M12 Connector

TE Internal #: T4171210504-001

Standard Circular Connectors, Wire-to-Panel, 4 Position, Sealable,

Wire & Cable, Signal, Reverse Gender, Nickel, Brass, M12

Connector

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors > M12 Panel Mount Wire











Connector System: Wire-to-Panel

Number of Positions: 4

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 4A

Keying & Polarized Position Locations

Factory Installed Backshell

All M12 Panel Mount Wire (66)

Features

Product Type Features

Prewired	Yes
Product Type	Connector Assembly
Accessory Color	Black
Assembly Type	Electrical Connector
Connector System	Wire-to-Panel
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Plug
Shell Type	Metal
Configuration Features	

D

No

D

Keying



Number of Positions	4
Number of Power Positions	0
Number of Signal Positions	4
Contacts Preloaded	Yes
Electrical Characteristics	
Operating Voltage	250 VAC
Body Features	
Peripheral Seal Material	Silicone
O-Ring Material	Silicone
Environmental Protection Type	Sealed
Shell Plating Material	Nickel
Shell Base Material	Brass
Circular Connector Insulation Material Type	Polyamide
Contact Features	
Contact Current Rating (Max)	4 A
Reverse Gender	Yes
Circular Connector Contact Type	Pin
Mechanical Attachment	
Polarization Code	D
Mating Alignment Type	Keyed
Housing Features	
Circular Connector Shell Size	18
Dimensions	
Wire Size	$.345 \text{ mm}^2$
Usage Conditions	
IP Water Sealing Level	IP67
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Signal
Shielded	No
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Polarization Code Mating Alignment Type Housing Features Circular Connector Shell Size Dimensions Wire Size Usage Conditions IP Water Sealing Level Operating Temperature Range Operation/Application	Yes Pin D Keyed 18 .34 – .5 mm² IP67 -40 – 85 °C[-40 – 185 °F]



UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	1
Other	
Field Serviceable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (1.9% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





Also in the Series M12 Connector





Customers Also Bought







Documents

Product Drawings

M12,FRONT MOUNTING,MALE,D,4P,0.2M WIRE

English

CAD Files

Customer View Model

ENG_CVM_CVM_T4171210504-001_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4171210504-001_B.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_T4171210504-001_B.2d_dxf.zip

English

3D PDF

Standard Circular Connectors, Wire-to-Panel, 4 Position, Sealable, Wire & Cable, Signal, Reverse Gender, Nickel, Brass, M12 Connector



3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications

Application Specification

English

Agency Approvals

UL

English