MMBT2369LT1, MMBT2369ALT1

MMBT2369ALT1 is a Preferred Device

Switching Transistors

NPN Silicon

ON Semiconductor®

http://onsemi.com

Features

- Pb−Free Packages are Available

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	15	Vdc
Collector−Emitter Voltage	V_{CES}	40	Vdc
Collector−Base Voltage	V_{CBO}	40	Vdc
Emitter−Base Voltage	V_{EBO}	4.5	Vdc
Collector Current − Continuous	I_C	200	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR−5 Board (Note 1) T_A = 25°C Derate above 25°C	P_D	225 1.8	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	556	°C/W
Total Device Dissipation Alumina Substrate, (Note 2) T_A = 25°C Derate above 25°C	P_D	300 2.4	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	417	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. FR−5 = 1.0 × 0.75 × 0.062 in.
2. Alumina = 0.4 × 0.3 × 0.024 in. 99.5% alumina.

SOT−23
CASE 318
STYLE 6

MARKING DIAGRAMS

xxx = M1J or 1JA
M = Date Code*
▪ = Pb−Free Package
(Note: Microdot may be in either location)
*Date Code orientation and/or overbar may vary depending upon manufacturing location.

ORDERING INFORMATION

Device	Package	Shipping
MMBT2369LT1	SOT−23	3000/Tape & Reel
MMBT2369LT1G	SOT−23 (Pb−Free)	3000/Tape & Reel
MMBT2369ALT1	SOT−23	3000/Tape & Reel
MMBT2369ALT1G	SOT−23 (Pb−Free)	3000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Preferred devices are recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2006

January, 2006 − Rev. 4
Publication Order Number:
MMBT2369LT1/D

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector−Emitter Breakdown Voltage (Note 3) (I_C = 10 mAdc, I_B = 0)		$V_{(BR)CEO}$	15	–	–	Vdc
Collector−Emitter Breakdown Voltage (I_C = 10 μAdc, V_{BE} = 0)		$V_{(BR)CES}$	40	–	–	Vdc
Collector−Base Breakdown Voltage (I_C = 10 μAdc, I_E = 0)		$V_{(BR)CBO}$	40	–	–	Vdc
Emitter−Base Breakdown Voltage (I_E = 10 μAdc, I_C = 0)		$V_{(BR)EBO}$	4.5	–	–	Vdc
Collector Cutoff Current (V_{CB} = 20 Vdc, I_E = 0) (V_{CB} = 20 Vdc, I_E = 0, T_A = 150°C)		I_{CBO}	– –	– –	0.4 30	μAdc
Collector Cutoff Current (V_{CE} = 20 Vdc, V_{BE} = 0)	MMBT2369A	I_{CES}	–	–	0.4	μAdc
ON CHARACTERISTICS						
DC Current Gain (Note 3) (I_C = 10 mAdc, V_{CE} = 1.0 Vdc) (I_C = 10 mAdc, V_{CE} = 1.0 Vdc) (I_C = 10 mAdc, V_{CE} = 0.35 Vdc) (I_C = 10 mAdc, V_{CE} = 0.35 Vdc, T_A = −55°C) (I_C = 30 mAdc, V_{CE} = 0.4 Vdc) (I_C = 100 mAdc, V_{CE} = 2.0 Vdc) (I_C = 100 mAdc, V_{CE} = 1.0 Vdc)	 MMBT2369 MMBT2369A MMBT2369A MMBT2369A MMBT2369A MMBT2369 MMBT2369A	h_{FE}	 40 – 40 20 30 20 20	 – – – – – – – –	 120 120 – – – – – –	–
Collector−Emitter Saturation Voltage (Note 3) (I_C = 10 mAdc, I_B = 1.0 mAdc) (I_C = 10 mAdc, I_B = 1.0 mAdc) (I_C = 10 mAdc, I_B = 1.0 mAdc, T_A = +125°C) (I_C = 30 mAdc, I_B = 3.0 mAdc) (I_C = 100 mAdc, I_B = 10 mAdc)	 MMBT2369 MMBT2369A MMBT2369A MMBT2369A MMBT2369A	$V_{CE(sat)}$	 – – – – –	 – – – – –	 0.25 0.20 0.30 0.25 0.50	Vdc
Base−Emitter Saturation Voltage (Note 3) (I_C = 10 mAdc, I_B = 1.0 mAdc) (I_C = 10 mAdc, I_B = 1.0 mAdc, T_A = −55°C) (I_C = 30 mAdc, I_B = 3.0 mAdc) (I_C = 100 mAdc, I_B = 10 mAdc)	 MMBT2369A MMBT2369A MMBT2369A MMBT2369A	$V_{BE(sat)}$	 0.7 – – –	 – – – –	 0.85 1.02 1.15 1.60	Vdc
SMALL−SIGNAL CHARACTERISTICS						
Output Capacitance (V_{CB} = 5.0 Vdc, I_E = 0, f = 1.0 MHz)		C_{obo}	–	–	4.0	pF
Small Signal Current Gain (I_C = 10 mAdc, V_{CE} = 10 Vdc, f = 100 MHz)		h_{fe}	5.0	–	–	–
SWITCHING CHARACTERISTICS						
Storage Time (I_{B1} = I_{B2} = I_C = 10 mAdc)		t_s	–	5.0	13	ns
Turn−On Time (V_{CC} = 3.0 Vdc, I_C = 10 mAdc, I_{B1} = 3.0 mAdc)		t_{on}	–	8.0	12	ns
Turn−Off Time (V_{CC} = 3.0 Vdc, I_C = 10 mAdc, I_{B1} = 3.0 mAdc, I_{B2} = 1.5 mAdc)		t_{off}	–	10	18	ns

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

SWITCHING TIME EQUIVALENT TEST CIRCUITS FOR 2N2369, 2N3227

*Total shunt capacitance of test jig and connectors.

Figure 1. t_{on} Circuit − 10 mA

Figure 3. t_{off} Circuit − 10 mA

*Total shunt capacitance of test jig and connectors.

Figure 2. t_{on} Circuit − 100 mA

Figure 4. t_{off} Circuit − 100 mA

Figure 5. Turn−On and Turn−Off Time Test Circuit

Figure 6. Junction Capacitance Variations

Figure 7. Typical Switching Times

Figure 8. Maximum Charge Data

Figure 9. Q_T Test Circuit

Figure 10. Turn−Off Waveform

Figure 11. Storage Time Equivalent Test Circuit

Figure 12. Maximum Collector Saturation Voltage Characteristics

Figure 13. Minimum Current Gain Characteristics

Figure 14. Saturation Voltage Limits

Figure 15. Typical Temperature Coefficients

PACKAGE DIMENSIONS

SOT−23 (TO−236)
CASE 318−08
ISSUE AN

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. 318−01 THRU −07 AND −09 OBSOLETE, NEW STANDARD 318−08.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.89	1.00	1.11	0.035	0.040	0.044
A1	0.01	0.06	0.10	0.001	0.002	0.004
b	0.37	0.44	0.50	0.015	0.018	0.020
c	0.09	0.13	0.18	0.003	0.005	0.007
D	2.80	2.90	3.04	0.110	0.114	0.120
E	1.20	1.30	1.40	0.047	0.051	0.055
e	1.78	1.90	2.04	0.070	0.075	0.081
L	0.10	0.20	0.30	0.004	0.008	0.012
L1	0.35	0.54	0.69	0.014	0.021	0.029
H_E	2.10	2.40	2.64	0.083	0.094	0.104

STYLE 6:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

SOLDERING FOOTPRINT*

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 61312, Phoenix, Arizona 85082−1312 USA
Phone: 480−829−7710 or 800−344−3860 Toll Free USA/Canada
Fax: 480−829−7709 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center
2−9−1 Kamimeguro, Meguro−ku, Tokyo, Japan 153−0051
Phone: 81−3−5773−3850

ON Semiconductor Website: http://onsemi.com

Order Literature: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.