


CAB650M17HM3

1700 V, 650 A, Silicon Carbide, Half-Bridge Module

V_{DS}	1700 V
I_{DS}	650 A

Technical Features

- Ultra-Low Loss
- High Frequency Operation
- Zero Turn-Off Tail Current from MOSFET
- Normally-Off, Fail-Safe Device Operation



Applications

- Railway, Traction, and Motor Drives
- EV Chargers
- High-Efficiency Converters / Inverters
- Renewable Energy
- Smart-Grid / Grid-Tied Distributed Generation

System Benefits

- Enables Compact, Lightweight Systems
- Increased System Efficiency, due to Low Switching & Conduction Losses of SiC
- Reduced Thermal Requirements and System Cost

Maximum Parameters (Verified by Design)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions	Note
Drain-Source Voltage	V _{DS}			1700	V		Fig. 33
Gate-Source Voltage, Maximum Value	V _{GS max}	-8		+19		Transient, <100 ns	
Gate-Source Voltage, Recommended	V _{GS op}	-4		+15		Static	
DC Continuous Drain Current	I _D		916		A	V _{GS} = 15 V, T _C = 25 °C, T _{VJ} ≤ 175 °C	Fig. 20
			694			V _{GS} = 15 V, T _C = 90 °C, T _{VJ} ≤ 175 °C	
DC Source-Drain Current (Body Diode)	I _{SD BD}		593			V _{GS} = -4 V, T _C = 25 °C, T _{VJ} ≤ 175 °C	
			382			V _{GS} = -4 V, T _C = 90 °C, T _{VJ} ≤ 175 °C	
Pulsed Drain Current	I _{D (pulsed)}			1300	°C	t _{Pmax} limited by T _{VJmax} V _{GS} = 15 V, T _C = 25 °C	
Virtual Junction Temperature	T _{VJ op}	-40		175		Operation	

MOSFET Characteristics (Per Position) ($T_{VJ} = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions	Note
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	1700			V	$V_{GS} = 0 \text{ V}, T_{VJ} = -40^\circ\text{C}$	
Gate Threshold Voltage	$V_{GS(\text{th})}$	1.8	2.5	3.6		$V_{DS} = V_{GS}, I_D = 305 \text{ mA}$	
			2.0			$V_{DS} = V_{GS}, I_D = 305 \text{ mA}, T_{VJ} = 175^\circ\text{C}$	
Zero Gate Voltage Drain Current	I_{DSS}		12	500	μA	$V_{GS} = 0 \text{ V}, V_{DS} = 1700 \text{ V}$	
Gate-Source Leakage Current	I_{GSS}		0.012	3		$V_{GS} = 15 \text{ V}, V_{DS} = 0 \text{ V}$	
Drain-Source On-State Resistance (Devices Only)	$R_{DS(\text{on})}$		1.42	1.86	$\text{m}\Omega$	$V_{GS} = 15 \text{ V}, I_D = 650 \text{ A}$	Fig. 2 Fig. 3
			3.26			$V_{GS} = 15 \text{ V}, I_D = 650 \text{ A}, T_{VJ} = 175^\circ\text{C}$	
Transconductance	g_{fs}		553		S	$V_{DS} = 20 \text{ V}, I_D = 650 \text{ A}$	Fig. 4
			561			$V_{DS} = 20 \text{ V}, I_D = 650 \text{ A}, T_{VJ} = 175^\circ\text{C}$	
Turn-On Switching Energy, $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$ $T_{VJ} = 175^\circ\text{C}$	E_{On}		38.8 44.0 50.8		mJ	$V_{DD} = 900 \text{ V}$ $I_D = 650 \text{ A},$ $V_{GS} = -4 \text{ V}/15 \text{ V},$ $R_{G(OFF)} = 1.5 \Omega, R_{G(ON)} = 1.5 \Omega,$ $L = 14 \mu\text{H}$	Fig. 11 Fig. 13
Turn-Off Switching Energy, $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$ $T_{VJ} = 175^\circ\text{C}$	E_{off}		25.6 26.2 27.6				
Internal Gate Resistance	$R_{G(\text{int})}$		0.62		Ω	$f = 1 \text{ MHz}, V_{AC} = 25 \text{ mV}$	
Input Capacitance	C_{iss}		97.3		$n\text{F}$	$V_{GS} = 0 \text{ V}, V_{DS} = 1200 \text{ V}$ $V_{AC} = 25 \text{ mV}, f = 100 \text{ kHz}$	Fig. 9
Output Capacitance	C_{oss}		2.3				
Reverse Transfer Capacitance	C_{rss}		63		pF		
Gate to Source Charge	Q_{GS}		960		$n\text{C}$	$V_{DS} = 1200 \text{ V}, V_{GS} = -4 \text{ V}/15 \text{ V}$ $I_D = 1100 \text{ A}$ Per IEC60747-8-4 pg 21	
Gate to Drain Charge	Q_{GD}		840				
Total Gate Charge	Q_G		2988				
FET Thermal Resistance, Junction to Case	$R_{th JC}$		0.054		$^\circ\text{C/W}$		Fig. 17

Diode Characteristics (Per Position) ($T_{VJ} = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions	Notes
Body Diode Forward Voltage	V_{SD}		5.4		V	$V_{GS} = -4 \text{ V}, I_{SD} = 650 \text{ A}$	Fig. 7
			4.7			$V_{GS} = -4 \text{ V}, I_{SD} = 650 \text{ A}, T_{VJ} = 175^\circ\text{C}$	
Reverse Recovery Time	t_{RR}		83		ns	$V_{GS} = -4 \text{ V}, I_{SD} = 650 \text{ A}, V_R = 900 \text{ V}$ $di/dt = 13 \text{ A/ns}, T_{VJ} = 175^\circ\text{C}$	Fig. 32
Reverse Recovery Charge	Q_{RR}		24				
Peak Reverse Recovery Current	I_{RRM}		420				
Reverse Recovery Energy, $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$ $T_{VJ} = 175^\circ\text{C}$	E_{RR}		0.9 5.3 9.2		mJ	$V_{DD} = 900 \text{ V}, I_D = 650 \text{ A},$ $V_{GS} = -4 \text{ V}/15 \text{ V}, R_{G(ON)} = 1.5 \Omega,$ $L = 14 \mu\text{H}$	Fig. 14



Module Physical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Package Resistance, M1 (High-Side)	R ₁₋₂		106.5		$\mu\Omega$	T _C = 125°C, Note 1
Package Resistance, M2 (Low-Side)	R ₂₋₃		126.3			T _C = 125°C, Note 1
Stray Inductance	L _{Stray}		4.9		nH	Between DC- and DC+, f = 10 MHz
Case Temperature	T _C	-40		125	°C	
Mounting Torque	M _S	3 0.9	4.5 1.1	5 1.3	N·m	Baseplate, M6 bolts Power Terminals, M4 bolts
Weight	W		167			
Case Isolation Voltage	V _{isol}	4			kV	AC, 50 Hz, 1 minute
Comparative Tracking Index	CTI	600				
Clearance Distance		13.07 6.00			mm	Terminal to Terminal Terminal to Heatsink
Creepage Distance		14.27 12.34				Terminal to Terminal Terminal to Heatsink

Note:

¹Total Effective Resistance (Per Switch Position) = MOSFET R_{DS(on)} + Switch Position Package Resistance

NTC Characteristics (T_{NTC} = 25 °C unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Resistance at 25°C	R ₂₅		4700		Ω	
Tolerance of R ₂₅			±1		%	
Beta Value for 25°C to 85°C	B _{25/85}		3435		K	
Beta Value for 0°C to 100°C	B _{0/100}		3399		K	
Tolerance of B _{25/85}			±1		%	
Maximum Power Dissipation	P _{Max}		50		mW	

Steinhart & Hart Coefficients for NTC Resistance & NTC Temperature Computation (T in K)







$$\ln\left(\frac{R}{R_{25}}\right) = A + \frac{B}{T} + \frac{C}{T^2} + \frac{D}{T^3}$$

A	B	C	D
-1.289E+01	4.245E+03	-8.749E+04	-9.588E+06

$$\frac{1}{T} = A_1 + B_1 \ln\left(\frac{R}{R_{25}}\right) + C_1 \ln^2\left(\frac{R}{R_{25}}\right) + D_1 \ln^3\left(\frac{R}{R_{25}}\right)$$

A ₁	B ₁	C ₁	D ₁
3.354E-03	3.001E-04	5.085E-06	2.188E-07

Typical Performance



Typical Performance




Figure 7. 3rd Quadrant Characteristic vs. Junction Temperatures at $V_{GS} = -4$ V (Body Diode)




Figure 8. Typical Capacitances vs. Drain to Source Voltage (0 - 200V)




Figure 9. Typical Capacitances vs. Drain to Source Voltage (0 - 1200V)




Figure 10. Threshold Voltage vs. Junction Temperature




Figure 11. Switching Energy vs. Drain Current ($V_{DD} = 900$ V)




Figure 12. Switching Energy vs. Drain Current ($V_{DD} = 1200$ V)

Typical Performance









Figure 17. MOSFET Junction to Case Transient Thermal Impedance, Z_{thJC} (°C/W)



Typical Performance




Figure 19. Reverse Bias Safe Operating Area (RBSOA)




Figure 20. Continuous Drain Current Derating vs. Case Temperature




Figure 21. Maximum Power Dissipation Derating vs. Case Temperature




Figure 22. Typical Output Current Capability vs. Switching Frequency (Inverter Application)










Figure 23. NTC Resistance vs. NTC Temperature

Timing Characteristics



Definitions




Figure 30. Turn-off Transient Definitions




Figure 31. Turn-on Transient Definitions




Figure 32. Reverse Recovery Definitions






Figure 33. V_{GS} Transient Definitions



Schematic and Pin Out




PIN OUT SCHEME	
PIN	LABEL
①	V+
②	Mid
③	V-
④	G1, Top row pins (2)
⑤	K1, Bottom row pins (2)
⑥	G2, Top row pins (2)
⑦	K2, Bottom row pins (2)
⑧	NTC1
⑨	NTC2



Package Dimension (mm)



DIMENSION TABLE		
SYMBOL	DIMENSION	TOLERANCE
A1	110.00	± 0.60
A2	109.25	± 0.60
A3	65.00	± 0.60
A4	64.25	± 0.60
A5	3.25	± 0.30
A6	11.45	± 0.60
B1	93.00	± 0.30
B2	48.00	± 0.30
C1	11.30	± 0.40
C2	13.84	± 0.40
C3	24.00	± 0.40
C4	34.16	± 0.40
C5	36.70	± 0.40
C6	1.71	± 0.40
C7	17.30	± 0.50
C8	2.54	± 0.30
C9	0.64	± 0.30
C10	10.16	± 0.40
D1	23.75	± 0.50
D2	23.13	± 0.50
D3	24.13	± 0.50
D4	12.20	± 0.50
D5	71.00	± 0.30
D6	10.75	± 0.30



DETAIL A
SCALE: 4:1



Supporting Links & Tools

Evaluation Tools & Support

- CAB650M17HM3 PLECS Model
- SpeedFit 2.0 Design Simulator™
- Technical Support Forum
- Dynamic Characterization Evaluation Tool for the High Performance 62mm (HM) Module Platform

Dual-Channel Gate Driver Board

- CGD1700HB3P-HM3: Wolfspeed Gate Driver Board
- CGD12HB00D: Differential Transceiver Daughter Board Companion Tool for Differential Gate Drivers

Application Notes

- CPWR-AN35: 62mm Thermal Interface Material Application Note
- CPWR-AN39: KIT-CRD-CIL12N-HM User Guide
- PRD-04814: Design Options for Wolfspeed® Silicon Carbide MOSFET Gate Bias Power Supplies



Notes & Disclaimer

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by Cree. No communication from any employee or agent of Cree or any third party shall effect an amendment or modification of this document. No responsibility is assumed by Cree for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Cree.

Notwithstanding any application-specific information, guidance, assistance, or support that Cree may provide, the buyer of this product is solely responsible for determining the suitability of this product for the buyer's purposes, including without limitation for use in the applications identified in the next bullet point, and for the compliance of the buyers' products, including those that incorporate this product, with all applicable legal, regulatory, and safety-related requirements.

This product has not been designed or tested for use in, and is not intended for use in, applications in which failure of the product would reasonably be expected to cause death, personal injury, or property damage, including but not limited to equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment, aircraft navigation, communication, and control systems, aircraft power and propulsion systems, air traffic control systems, and equipment used in the planning, construction, maintenance, or operation of nuclear facilities.

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Cree representative or from the Product Documentation sections of www.cree.com.

REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your Cree representative to ensure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

Contact info:

4600 Silicon Drive
Durham, NC 27703 USA
Tel: +1.919.313.5300
www.wolfspeed.com/power