


7-Port USB 2.0 Hub


MODEL NUMBER: U223-007











Description

Tripp Lite's U223-007, 7-port USB 2.0 hub is the most versatile and powerful hub on the market. It allows you to connect up to seven USB devices to a single USB port on your computer. This unit meets or exceeds USB 2.0 Specifications for Hi-Speed data transmission rates up to 480Mbps. Perfect for both the mobile and desktop user. While the hub will function perfectly in virtually all cases without needing external power, a compact, multi-voltage AC adapter (110/220V) has been provided for the rare circumstance when connecting a power hungry device. This USB 2.0 device is backwards compatible so that it will function with both USB 2.0 and USB 1.1 devices. Over-current protection safeguards connected equipment from overvoltages.

Features

- USB2.0 7-Port Hub
- Supports data transfer rates up to 480Mbps
- Connect up to 7 USB devices to a single USB port on your computer
- Compact design is ideal for use with a laptop/notebook computer
- Does not require external power, software, or complicated set-up procedures
- Plug-and-play/hot-swappable allows you to add or remove a device at any time
- Per-port overcurrent protection
- Bus-powered or self-powered
- Supports USB 2.0 spec up to 500mA per port
- On bus-power, 500mA from the USB 2.0 computer port is shared between the hub ports
- The included external power supply provides 2A of power, to be shared between the hub ports (up to 500mA per port)
- Compact, multi-voltage power supply (110/220V) provided
- · Compatible with all major operating systems

Specifications

OVERVIEW

Highlights

- Connects up to 7 USB 2.0 devices
- Bus-powered or optional AC adapter
- Compatible with all major operating systems

System Requirements

- USB 2.0 Computer Port
- USB Peripherals

Package Includes

- U223-007 USB 2.0 Hub
- User's Manual
- USB 2.0 Mini B male to USB 2.0 A male cable
- 5V/2A DC Power Supply Optional
- External Power Supply with 1-15P Plug (Input: 100-240V, 50/60Hz, 0.4A Max / Output: 5.0V, 2000mA)



PHYSICAL		
	Dide (1 Owei)	
USER INTERFACE, ALERTS & CONTROLS LED Indicators Blue (Power)		
Power Consumption (Watts)	0.3	
DC Barrel Plug	OD: 3.5 x 1.35 x 8mm, Positive Pin, Negative Sleeve	
External Power Supply Cord Length (m.)	1.2	
External Power Supply Cord Length (ft.)	4	
External Power Supply Output Specs (V / A)	5V / 2A	
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.4A	
External Power Supply Plug(s)	NEMA 1-15P North America	
Power Source Type	AC Adapter	
POWER		
Product Length (m.)	0.166	
Product Length (ft.)	0.544	
Product Length (cm.)	16.6	
Product Length (in.)	6.53	
Bus Powered	No	
Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240	
INPUT		
Data Ports Details	(7) USB-A - USB 2.0	
Data Ports	(7) USB A (FEMALE)	
DATA		
Mirror Mode	No	
Extended Mode	No	
Number of Monitors Supported	0	
VIDEO		
Host Connector	USB A (MALE)	
Technology	USB 2.0 (High Speed)	
Product Type	Hub	
UPC Code	037332185389	



Color	Black	
Material of Construction	ABS	
Included Mounting Accessories	No	
Shipping Dimensions (hwd / in.)	2.10 x 3.10 x 7.50	
Shipping Weight (lbs.)	0.70	
Unit Dimensions (hwd / in.)	0.600 x 6.500 x 1.300	
Unit Dimensions (hwd / cm)	16.6 x 3.33 x 1.6	
Unit Packaging Type	Вох	
Unit Weight (lbs.)	0.14	
Unit Weight (kg)	0.06	
ENVIRONMENTAL		
Operating Temperature Range	32 to 158 F (0 to 70 C)	
Storage Temperature Range	14 to 194 F (-10 to 90 C)	
Relative Humidity	10% to 90 % RH, Non-Condensing	
BTUs	1 BTU/Hr	
Power Provided to Connected Device(s)	5V 0.5A (2.5W) Output per USB port	
CONNECTIONS		
Number of Ports	7	
Side A - Connector 1	USB MINI-B 5-PIN (FEMALE)	
Side B - Connector 1	(7) USB A (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
Driver Required	No	
STANDARDS & COMPLIANCE		
External Power Supply Certifications	DOE; FCC; UL	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	







© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.