

## Housing - HC-B 48-TFL-96/O1PG36S - 1675188

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Sleeve housing, for single locking latch, height 96 mm, without screw connection, 1x Pg36, lateral cable entry



The illustration shows version, panel mounting base with and without protective cover



### Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	725.1 GRM
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Dimensions

Height	96 mm
Width	89 mm
Length	131.5 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	For contact inserts HC-B48, DD216, M
Design	B48
Housing type	Sleeve housings
Locking type	for single locking latch
Cable exit	Lateral
Screw connection	None

# Housing - HC-B 48-TFL-96/O1PG36S - 1675188

## Technical data

### General

Type of the screw connection	1x Pg36
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Approvals

### Approvals

---

Approvals

GOST

---

Ex Approvals

---

# Housing - HC-B 48-TFL-96/O1PG36S - 1675188

## Approvals

Approvals submitted

---

## Approval details



## Drawings

Dimensioned drawing

