


**DK-SERIES
DKR 35 24VUC 1A**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com



At just 6 mm wide, all components of the DKR minicouplers have an extremely narrow design. Weidmüller also offers 4 and 5 screw-connections, with a rated cross-section of 4 mm². The mini-coupler is suitable for a wide range of applications. It is used for the coupling of digital sensor/actuator signals with automation devices on the process level..

General ordering data

Order No.	8016610000
Part designation	DKR 35 24VUC 1A
Version	DK-SERIES, Relays, No. of contacts: 1, NO contact, Rated control voltage: 24 V UC ±10 %, Screw connection
GTIN (EAN)	4008190132804
Qty.	10 pc(s).

**DK-SERIES
DKR 35 24VUC 1A**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com

Technical data
Dimensions

Length	77 mm	Width	6 mm
Height	62 mm		

Temperature

Ambient temperature (operational)	-25 °C...+40 °C	Storage temperature	-40 °C...+60 °C
-----------------------------------	-----------------	---------------------	-----------------

Input

Rated voltage	150 V	Rated control voltage	24 V UC ±10 %
Response / drop-out voltage AC coil	12 V / 8 V	Pull-in (sparkover) / drop-out voltage DC coil	10 V / 11 V
Rated current AC	15 mA	Rated current DC	9 mA
Pull-in / drop-out current, AC coil	6.3 mA / 4.3 mA	Pull-in / drop-out current, DC coil	3.8 mA // 3mA
Power rating	0.36 VA / 216 mW	Status indicator	Green LED

Output

Continuous current	0.5 A	Max. switching current	500 A
Max. switching frequency at rated load	5 Hz	Sparkover time / Drop-out time	typ. 0.7...2.5 ms / 0.2...2 ms
Switch-off delay	typical. 0.2...2.0 ms	Switch-on delay	typically 0.7...2.5 ms
Switching voltage AC, max.	100 V	making current	500 mA
max. switching capacity	10 W / 10 VA	min. switching capacity	1 V / 1 mA

Contact data

Contact design	NO contact	No. of contacts	1
Contact material	Rh/Ru	Mechanical service life	10 ⁹ switching cycles

Rated data

Conductor connection system	Screw connection	DIN Rail compatibility	TS 35
Humidity	40°C / 93% rel. humidity, no condensation		

Insulation coordination (EN 50 178)

Clearance and creepage distances for control/load side	≥ 3 mm	Dielectric strength to mounting rail	4 kV _{eff}
Impulse withstand voltage	1.5 kV	Overvoltage category	III
Pollution severity	2	Protection class	IP 20
Protective separation acc. to VDE 0106 part 101	No	Rated voltage	150 V

Other technical data

Free-wheel diode	No	Reverse polarity protection	not available
Status indicator	Green LED	Version	Relay coupler

Approvals

Approvals institutes	GOSTME25; CE
----------------------	--------------

Datasheet**DK-SERIES
DKR 35 24VUC 1A**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Technical data**Classifications**

ETIM 2.0	EC001437	ETIM 3.0	EC001437
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01

Notes

Note, technical data	End plate AP DKT4 PA 0687560000
----------------------	------------------------------------

Datasheet

DK-SERIES
DKR 35 24VUC 1A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings

Electric symbol

